

NXP Secure Smart Card Controller N7121 with IC Dedicated Software and Crypto Library (R1/R2/R3/R4)

Security Target Lite

Rev. 3.4 — 9 December 2025
BSI-DSZ-CC-1136

Evaluation document
PUBLIC

Document information

Information	Content
Keywords	Common Criteria, Security Target, Security IC, N7121
Abstract	This document is the Security Target of the NXP Smart Card Controller N7121 with IC Dedicated Software. The document describes the security Functionality provided by the IC and its software.



Revision history

Table 1. Revision history

Version	Release date	Change notice
3.4	2025-12-09	Revision of ST Lite synced with full ST v3.4

1 Introduction

1.1 ST reference

NXP Secure Smart Card Controller N7121 with IC Dedicated Software and Crypto Library (R1/R2/R3/R4), Security Target Lite, Version 3.4, NXP Semiconductors, 9 December 2025.

1.2 TOE reference

The TOE is named NXP Secure Smart Card Controller N7121 with IC Dedicated Software and Crypto Library (R1/R2/R3/R4). In this document, the TOE is abbreviated to N7121. All components of the TOE and their respective version numbers are listed in [Section 1.4.1](#).

1.3 TOE overview

The TOE is the hard macro NXP Secure Smart Card Controller N7121 with IC Dedicated Software and Crypto Library (R1/R2/R3/R4), or in short N7121, which is manufactured in GlobalFoundries 40nm (C40) technology and comprises of hardware, software (security IC Dedicated Software), and documentation. The N7121 is self-sufficient at the boundary of the hard macro and can be instantiated within packaged products. The TOE does not include a customer-specific Security IC Embedded Software, however, it provides secure mechanisms for customers to download and execute their code on the TOE. For the sake of simplicity, in this Security Target, we refer to the IC hardware as *the hardware instantiation of the hard macro*.

1.3.1 Hardware

The IC hardware is a microcontroller incorporating a central processing unit (CPU), memories accessible via a Memory Management Unit (MMU), cryptographic coprocessors, other security components, contact-based and contactless communication interfaces as well as a general purpose I/O interface which can be used to directly use peripherals of the TOE such as the cryptographic coprocessors. The central processing unit supports a 32-/16-bit instruction set optimized for smart card applications. On-chip memories are ROM, RAM and Flash. The Flash can be used as data or program memory. It consists of highly reliable memory cells, which are designed to provide data integrity. The Flash memory is optimized for applications that require reliable non-volatile data storage for data and program code. Dedicated security functionality protects the contents of all memories. The logical Flash size can be configured in 1kB steps. The IC integrates coprocessors for AES, DES (both within the new Crypto2+ coprocessor) and a new 128 bit Public Key Crypto Coprocessor (Fame3) to support the implementation of asymmetric cryptographic algorithms.

Note: Please note that the Flash memory is also referred to as Non-Volatile Memory (NVM) in this Security Target.

The IC Embedded Software can either be located in ROM or Flash, see [Table 3](#).

1.3.2 Software

The IC Dedicated Software comprises IC Dedicated Test Software for test purposes and IC Dedicated Support Software. The IC Dedicated Support Software consists of the

Boot Software, which controls the boot process of the hardware platform. Furthermore, it provides a Firmware Interface and optionally a Library Interface, simplifying access to the hardware for the Security IC Embedded Software. The IC Dedicated Support Software also comprises optional software components, i.e.,

- two logical cards (A and B),
- a System Mode OS which offers ready-to-use resource and access management for customer applications that do not want to be exposed to the more low-level features of the TOE,
- the System Mode OS also provides a Secure User Mode Box, which further restricts the access of code executed in User Mode (UM),
- a Flash Loader OS which supports download of code and data to Flash by the Composite Product Manufacturer before Operational Usage (e.g. during development), and
- a crypto library which provides simplified access to frequently used cryptographic algorithms AES, TDES, RNG, RSA, ECC, hashing and Utilities.

The availability of these software components depends on the different TOE configurations defined in [Section 1.4.1](#).

1.3.3 Documentation

The documentation includes a Product Data Sheet with several addenda, an Instruction Set Manual, a Guidance and Operation Manual, User Manuals for cryptographic functions and Utilities as well as a Wafer and Delivery Specification. This documentation comprises a description of the architecture, the secure configuration and usage of the IC hardware platform and the IC Dedicated Support Software by the Security IC Embedded Software. As some parts of the IC Dedicated Support Software are optional, the respective documentation is optional as well and depends on the TOE configurations chosen by the customer. The dependencies and list of documentation is given in [Table 3](#).

1.3.4 Usage and major security functionality of the TOE

The security functionality of the TOE is designed to act as an integral part of a complete security system in order to strengthen the design as a whole. Several security mechanisms are completely implemented in and controlled by the TOE. Other security mechanisms allow for configuration by or even require support of the Security IC Embedded Software.

N7121 provides high security for smartcard applications and in particular for being used in the banking and finance market, in electronic commerce, or in governmental applications. Hence, the N7121 shall maintain

- the integrity and the confidentiality of code and data stored in its memories,
- the different TOE modes with the related capabilities for configuration and memory access, and
- the integrity, the correct operation and the confidentiality of security functionality provided by the TOE.

This is ensured by the construction of the TOE and its security functionality.

The N7121 basically provides a hardware platform and crypto library for an implementation of a smart card application with

- functionality to calculate Data Encryption Standard (Triple-DES) with 112-bit or 168-bit keys,

- functionality to calculate Advanced Encryption Standard (AES) with different key lengths,
- functionality to calculate RSA, RSA key generation, RSA public key computation,
- functionality to calculate ECDSA (ECC over GF(p)) signature generation and verification, ECDSA (ECC over GF(p)) key generation, ECDH (ECC Diffie-Hellmann) key-exchange, and full point addition(ECC over GF(p)) over any Weierstrass curves from size 128 bits to size 640 bits with co-factor equal 1,
- basic support of the PACE protocol ([\[TR-03110-1\]](#), [\[TR-03110-2\]](#), [\[TR-03110-3\]](#), [\[TR-03110-4\]](#)) as ECC base-point operations are protected against leakage and fault injection for the evaluated configuration of the TOE with Crypto Library release 0.7.7 only,
- KeyStore feature for secure key management,
- secure copy, move, and compare operations provided by the crypto library,
- functionality to compute SHA-1, SHA-224, SHA-256, SHA-384, and SHA-512,
- a True Random Number Generator,
- a Hybrid Deterministic Random Number Generator,
- a Hybrid Physical Random Number Generator,
- a Physical Unclonable Function (PUF),
- memory management control and memory encryption,
- physical protection via sensors on the chip and chip shielding, and
- two completely separated logical cards A and B, each with System Mode and User Mode.

Further functionality of the TOE which **does not correspond to security functionality** as defined in this Security Target is

- ISO/IEC 7816 contact interface with UART and ISO/IEC 14443A contactless interface,
- a general purpose communication interface which can be used to directly access peripherals of the TOE,
- an Undocumented Function (UDF), i.e., a proprietary operation used for data blinding, and
- cyclic redundancy check (CRC) calculation.
- KoreanSeed Library, providing cryptographic operations using the 128-bit block cipher SEED.

1.3.5 TOE type

The TOE NXP Secure Smart Card Controller N7121 with IC Dedicated Software and Crypto Library (R1/R2/R3/R4), or in short N7121, is provided as IC hardware platform with IC Dedicated Software for various operating systems and applications with high security requirements.

1.3.6 Required non-TOE hardware/software/firmware

Besides the conventional communication interfaces, the TOE provides a general purpose I/O interface. It is not required to use this interface, however, it can be used to access major security features of the TOE. This certification does not address the communication via the general purpose I/O interface, however, the TOE implements countermeasures against misuse.

1.4 TOE description

1.4.1 Evaluated configurations and TOE components

The TOE features different types of memories, some are configurable to the customer others are fixed, as shown in the following table.

Table 2. Memories of the TOE

Memory type	Memory size	Description
NVM	configurable up to 344 KBytes	The size of the Non-Volatile Memory.
ROM	Configurable to 0 KBytes or 150 KBytes	Size of the Read-Only Memory.
RAM	12 KBytes	Size of the Random-Access Memory. Size available to customer depends on ordered configuration (e.g., availability of MIFARE).

The TOE provides different configuration options a customer can make in the ordering process (Ordering Configurations). The following table lists configurations with impact on the security functionality.

Default values are indicated as **bold text**.

Table 3. TOE configuration options

Product option	Choices	Description
Ordering configurations		
NVM Size	configurable in 1kB steps up to 344 KBytes	The Flash memory size is logically configurable, within the given step size. Note: <i>If utilized, the Flashloader occupies 16 kB of storage, which are freed up after its usage.</i>
Customer Type	<ul style="list-style-type: none"> System Mode customer User Mode customer 	Depending on this choice, the customer has access to the System Mode of the logical card B (System Mode customer) or not (User Mode customer). In the first case, customers can store the Security IC Embedded Software in the System Mode of the logical card B. Otherwise, the NXP System Mode OS is placed on each available logical card in System Mode, while the customer can only access the less privileged User Mode.
Use Flash Loader	<ul style="list-style-type: none"> Yes No 	Depending on this choice, the TOE provides the functionality of a Flash Loader such that customers can load their code to the NVM memory. If the Flash Loader is available, the Library Interface and the N7121 Crypto Library become mandatory. If the Flash Loader is not available, the customer can still decide whether the Security IC Embedded Software will be stored in ROM or Flash during the development process. The Security IC Embedded Software is then programmed to Flash by NXP and using the Flash Loader which will be removed afterward.

Beside the above configurations, further Ordering Configurations are possible. However, these do not affect the Security Functionality defined in this ST. These configurations are listed below to provide a full picture:

Ordering Configurations without security impact:

- User ID settings,
- different options for contact-based and contactless communication,
- available data rates (106kbit/s, 106-848kbit/s, 106-848kbit/s and VHBR rates up to 3.2Mbit/s, or all),
- ATS/ATR check during testing,
- Enable or disable Chip Health Mode (CHM).

The TOE does not provide any functionality to tailor its available security functionality after delivery.

In case MIFARE DESFire or MIFARE Plus functionality has been ordered by the customer, the following MIFARE memory configurations are possible via Post-Delivery Configuration (PDC), which have no impact on the security functionality provided by the TOE:

- MIFARE DESFire EV2 (2K, 4K, 8K, 16K, 24K, 32K, or disabled) (resides in UM of card A) and
- MIFARE Plus EV1 (2K, 4K, or disabled) (resides in UM of card A).

Configurations containing MIFARE Plus or MIFARE DESFire are only certified on devices preconfigured by NXP with a dual-interface and with 340kB of NVM available, as specified in [\[DSheet_OEF\]](#).

Note:

Logical card A provides MIFARE DESFire and/or MIFARE Plus in its User Mode. The MIFARE Software does not provide any security functionality defined in this Security Target. The NXP SM OS is mandatory on Card A and cannot be replaced or changed. It configures the Memory Management Unit in such a way that software running in User Mode of Card A cannot interfere with other software running on the TOE and related memories on the TOE if not explicitly allowed. This functionality is called "NXP Secure User Mode Box". In case no MIFARE DESFire or MIFARE Plus functionality is ordered by the customer, the memory space of the User Mode in logical card A is set to zero.

Note:

The CHM can be used for chip identification, application of post-delivery configurations, and functional self-tests of the TOE. If the CHM is not available, chip identification and post-delivery configurations is still available, however, a customer has to spend more effort to access the respective functionality. The functional self-tests which are available in the CHM are not part of the Security Functionality defined in this ST.

Depending on the customer choices, the N7121 comprises the following deliverables:

Table 4. TOE deliverables of the hard macro

Type	Name	Release	Form of delivery
TOE components for all configurations (R1/R2/R3/R4)			
IC Hardware	N7121	B1	Hard macro instantiated within a wafer, modules and/or package.

Table 4. TOE deliverables of the hard macro...continued

Type	Name	Release	Form of delivery
IC Dedicated Test Software	Test Software	9.2.3.0	On-chip software
IC Dedicated Support Software	Boot Software	9.2.3.0	On-chip software
	Firmware	9.2.3.0	On-chip software
Document	<i>NXP Secure Smart Card Controller N7121 – Overview</i> , Product data sheet [DSheet]	3.3	Electronic document (PDF via NXP DocStore)
Document	<i>N7121 Wafer and delivery specification</i> , Product data sheet addendum [DSheet_WDS]	3.3	Electronic document (PDF via NXP DocStore)
Document	<i>SmartMX3 family P71D321 Dedicated type creation</i> , Product data sheet addendum [DSheet_OEF]	3.2	Electronic document (PDF via NXP DocStore)
Document	<i>NXP Secure Smart Card Controller N7121 – Instruction Set Manual</i> , Product data sheet addendum [DSheet_InSet]	3.1	Electronic document (PDF via NXP DocStore)
Document	<i>NXP Secure Smart Card Controller N7121 – Chip Health Mode</i> , Product data sheet addendum [DSheet_CHM]	3.1	Electronic document (PDF via NXP DocStore)
Document	<i>NXP Secure Smart Card Controller N7121 – Peripheral Configuration and Use</i> , Product data sheet addendum [DSheet_Periph]	3.2	Electronic document (PDF via NXP DocStore)
Document	<i>NXP Secure Smart Card Controller N7121 – MMU Configuration and NXP Firmware Interface Specification</i> , Product data sheet addendum [DSheet_MMU]	3.7	Electronic document (PDF via NXP DocStore)
Document	<i>UM12352, N7121 Information on Guidance and Operation</i> , User manual [GOM]	3.4	Electronic document (PDF via NXP DocStore)
Document ^[1]	<i>NXP N7121 B1 Hardmarco - Lifecycle Documentation</i> , Report [Lifecycle]	1.30	Electronic document (PDF via NXP DocStore)
Deliverables of the Flash Loader OS for all configurations (R1/R2/R3/R4)			
IC Dedicated Support Software	Flashloader OS	1.2.5	On-chip software
Document	<i>NXP Secure Smart Card Controller N7121 – Flashloader OS</i> , Product data sheet addendum [DSheet_FL]	3.0	Electronic document (PDF via NXP DocStore)
Deliverables of the Library Interface for all configurations (R1/R2/R3/R4)			
IC Dedicated Support Software	Library Interface	9.2.3.0	On-chip software
Library	Communication Library	6.0.0	Electronic files (object files via NXP DocStore)

Table 4. TOE deliverables of the hard macro...continued

Type	Name	Release	Form of delivery
Library	CRC Library	1.1.8	Electronic files (object files via NXP DocStore)
Library	Memory Library	1.2.3	Electronic files (object files via NXP DocStore)
Library	Flash Loader Library	3.6.0	Electronic files (object files via NXP DocStore)
Document	<i>NXP Secure Smart Card Controller N7121 – Shared OS Libraries</i> , Product data sheet addendum [DSheet_LibInt]	3.2	Electronic document (PDF via NXP DocStore)
Deliverables of the System Mode OS (for UM customers or MIFARE customers) for all configurations (R1/R2/R3/R4)			
IC Dedicated Support Software	System Mode OS ^[2]	13.2.3.0	On-chip software
Document	<i>NXP Secure Smart Card Controller N7121 – NXP System Mode OS</i> , Product data sheet addendum [DSheet_SMOS]	3.6	Electronic document (PDF via NXP DocStore)
Deliverables for Card-A Developer (NXP) for all configurations (R1/R2/R3/R4) ^[3]			
Document	<i>NXP Secure Smart Card Controller N7121</i> , Specification and Design Documentation [Spec_and_Design]	1.0	Electronic document (PDF via Internal NXP network)
Deliverables of the crypto library for configurations R1/R2/R3			
IC Dedicated Support Software	Crypto Library	0.7.6	On-chip software
Package Random Number Generation			
Library	RNG Lib	0.7.6	Electronic files (object files via NXP DocStore)
Library	RNG HealthTest Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – RNG Library</i> , User Manual [UM_RNG]	1.2	Electronic document (PDF via NXP DocStore)
Package Symmetric Ciphers			
Library	Sym. Cipher Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – Symmetric Cipher Library (SymCfg)</i> , Preliminary user manual [UM_SymCfg]	1.4	Electronic document (PDF via NXP DocStore)
Package KeyStore			

Table 4. TOE deliverables of the hard macro...continued

Type	Name	Release	Form of delivery
Library	KeyStoreMgr Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – KeyStoreMgr Library</i> , User Manual [UM_KeyStore]	1.1	Electronic document (PDF via NXP DocStore)
TOE components required for the packages Random Number Generation and Symmetric Ciphers			
Library	Sym. Utilities Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – Utils Library</i> , User Manual [UM_SymUtils]	1.1	Electronic document (PDF via NXP DocStore)
Package RSA Encryption / Decryption			
Library	RSA Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – RSA Library</i> , User Manual [UM_RSA]	1.4	Electronic document (PDF via NXP DocStore)
Package RSA Key Generation			
Library file	RSA Key Generation Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – RSA Key Generation Library</i> , User Manual [UM_RSAKeyGen]	1.3	Electronic document (PDF via NXP DocStore)
Package ECC over GF(p)			
Library	ECC Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – ECC over GF(p) Library</i> , User Manual [UM_ECC]	2.3	Electronic document (PDF via NXP DocStore)
Package SHA			
Library	SHA Library & Hash Library	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – SHA Library</i> , User Manual [UM_SHA]	1.1	Electronic document (PDF via NXP DocStore)
Document	<i>N7121 Crypto Library – HASH Library</i> , User Manual [UM_HASH]	1.2	Electronic document (PDF via NXP DocStore)
TOE components required for the packages RSA Encryption / Decryption, RSA Key Generation, ECC over GF(p), and SHA			

Table 4. TOE deliverables of the hard macro...continued

Type	Name	Release	Form of delivery
Library	Asym. Utilities Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – UtilsAsym Library</i> , User Manual [UM_AsymUtils]	1.3	Electronic document (PDF via NXP DocStore)
Package KoreanSeed			
Library	KoreanSeed Lib	0.7.6	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – KoreanSeed Library</i> , User Manual [UM_KoreanSeed]	1.1	Electronic document (PDF via NXP DocStore)
TOE components required for all packages			
Document	<i>UM12237: Information on Guidance and Operation</i> , User manual [GOM_CL]	4.2	Electronic document (PDF via NXP DocStore)
Additional deliverables of the crypto library for configuration R4 only			
IC Dedicated Support Software	Crypto Library	0.7.7	On-chip software
Package Random Number Generation			
Library	RNG Lib	0.7.7	Electronic files (object files via NXP DocStore)
Library	RNG HealthTest Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – RNG Library</i> , User Manual [UM_RNG]	1.2	Electronic document (PDF via NXP DocStore)
Package Symmetric Ciphers			
Library	Sym. Cipher Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – Symmetric Cipher Library (SymCfg)</i> , Preliminary user manual [UM_SymCfg]	1.4	Electronic document (PDF via NXP DocStore)
Package KeyStore			
Library	KeyStoreMgr Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – KeyStoreMgr Library</i> , User Manual [UM_KeyStore]	1.1	Electronic document (PDF via NXP DocStore)
TOE components required for the packages Random Number Generation and Symmetric Ciphers			

Table 4. TOE deliverables of the hard macro...continued

Type	Name	Release	Form of delivery
Library	Sym. Utilities Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	N7121 Crypto Library – Utils Library, User Manual [UM_SymUtils]	1.1	Electronic document (PDF via NXP DocStore)
Package RSA Encryption / Decryption			
Library	RSA Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	N7121 Crypto Library – RSA Library, User Manual [UM_RSA]	1.4	Electronic document (PDF via NXP DocStore)
Package RSA Key Generation			
Library file	RSA Key Generation Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	N7121 Crypto Library – RSA Key Generation Library, User Manual [UM_RSAKeyGen]	1.3	Electronic document (PDF via NXP DocStore)
Package ECC over GF(p)			
Library	ECC Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	N7121 Crypto Library – ECC over GF(p) Library, User Manual [UM_ECC]	2.4	Electronic document (PDF via NXP DocStore)
Package SHA			
Library	SHA Library & Hash Library	0.7.7	Electronic files (object files via NXP DocStore)
Document	N7121 Crypto Library – SHA Library, User Manual [UM_SHA]	1.1	Electronic document (PDF via NXP DocStore)
Document	N7121 Crypto Library – HASH Library, User Manual [UM_HASH]	1.2	Electronic document (PDF via NXP DocStore)
TOE components required for the packages RSA Encryption / Decryption, RSA Key Generation, ECC over GF(p), and SHA			
Library	Asym. Utilities Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	N7121 Crypto Library – UtilsAsym Library, User Manual [UM_AsymUtils]	1.3	Electronic document (PDF via NXP DocStore)
Package KoreanSeed			

Table 4. TOE deliverables of the hard macro...continued

Type	Name	Release	Form of delivery
Library	KoreanSeed Lib	0.7.7	Electronic files (object files via NXP DocStore)
Document	<i>N7121 Crypto Library – KoreanSeed Library</i> , User Manual [UM_KoreanSeed]	1.1	Electronic document (PDF via NXP DocStore)
TOE components required for all packages			
Document	<i>UM12237: Information on Guidance and Operation</i> , User manual [GOM_CL]	4.2	Electronic document (PDF via NXP DocStore)

- [1] This guidance is available for NXP designers responsible for designing IO sidecar of a derived product only
- [2] In case MIFARE functionality has been ordered by the customer, the System Mode OS also contains the segment descriptors that setup the 'Secure User Mode Box' functionality in the User Mode of logical card A.
- [3] NXP develops and owns all code for Card-A. These deliverables are available for NXP only.

Note:

Although the N7121 is considered self-sufficient at the boundary of the hard macro, its IC Dedicated Software might require instantiation specific functionality for the packaged product on top of the hard macro related functionality. These instantiation specific IC Dedicated Software relates to both, IC Dedicated Test Software and IC Dedicated Support Software. The instantiation specific IC Dedicated Software is defined by the Wafer Test version and the IC Dedicated Firmware extension (see [\[DSheet_MMU\]](#) and [\[DSheet_SMOS\]](#)). Evaluated versions are given in [Table 5](#) and [Table 6](#).

Both release packages R1 and R2 consist of the relevant deliverables given in [Table 4](#) plus the instantiation specific IC Dedicated Software given in [Table 5](#) (R1) and [Table 6](#) (R2), respectively. It is important to note that, the release package R1 and R2 are only different in some functional improvements of IC Dedicated Software. There is no impact on the security functionalities claimed in this Security Target.

Both Release packages R1 and R2 are manufactured at GlobalFoundries Fab 7 in Singapore. Release package R3 is used to identify devices manufactured at GlobalFoundries Fab 1 in Dresden. The instantiation specific IC Dedicated Software for R3 devices is equal to either R1 or R2.

The release package R4 consists of the relevant deliverables given in [Table 4](#). Similar to the release package R3, The instantiation specific IC Dedicated Software for R1 and R2 are both applicable to R4. Last but not least, the release package R4 can be manufactured at either GlobalFoundries Fab 1 in Dresden or GlobalFoundries Fab 7 in Singapore.

Please note that, Crypto Library 0.7.7 introduces only an updated ECC library, an updated guidance and a new version of user manual for ECC library. All other libraries and guidance for Crypto Library 0.7.7 remain unchanged comparing to that of Crypto Library 0.7.6. The differences with respect to fabrication and Crypto Library deliverables are summarized in [Table 7](#)

Table 5. Instantiation specific IC Dedicated Software for Release package R1, R3 and R4

ID of Wafer Test version	ID of the IC Dedicated Firmware extensions
0x83	0x0

Table 5. Instantiation specific IC Dedicated Software for Release package R1, R3 and R4...continued

ID of Wafer Test version	ID of the IC Dedicated Firmware extensions
0x84	0x0
0x90	0x50

Table 6. Instantiation specific IC Dedicated Software for Release package R2, R3 and R4

ID of Wafer Test version	ID of the IC Dedicated Firmware extensions
0x85	0x0
0x87	0x1
0x92	0x51

Table 7. Fab and Crypto Library Deliverables for Release package R1, R2, R3 and R4

Release package	Fab	Crypto Library
R1/R2	GF7	Crypto Library 0.7.6, Crypto Library UGM v3.4 and ECC UM v2.3
R3	GF1	Crypto Library 0.7.6, Crypto Library UGM v3.4 and ECC UM v2.3
R4	GF1 and GF7	Crypto Library 0.7.7 (updated ECC library), Crypto Library UGM v3.5 and ECC UM v2.4

1.4.2 Physical scope of the TOE

The N7121 is manufactured in 40nm CMOS technology by GlobalFoundries and implemented as a hard macro. A block diagram of the IC hardware is depicted in [Figure 1](#).




Figure 1. Block diagram of the TOE

The N7121 consists of the IC hardware and IC Dedicated Software. The IC Dedicated Software is composed of IC Dedicated Test Software for test purposes and IC Dedicated Support Software. The IC Dedicated Support Software contains the Boot Software, the Firmware Interface, the Library Interface, the cryptographic libraries, the System Mode OS and the Flash Loader OS. All other software is called Security IC Embedded Software. The Security IC Embedded Software is not part of the TOE (Application Note 2 of [PP]).

Please note that not all parts of the IC are defined as TOE. In addition to the conventional contact-based and contactless communication interfaces, the TOE provides a general purpose I/O interface which is directly connected to the internal SFR bus. This interface can be connected to an I2C interface for instance which is not part of the evaluation. The Security Functionality of the TOE does not rely on the communication interface connected to this interface. However, the TOE implements countermeasures against misuse.

1.4.3 Logical scope of the TOE

1.4.3.1 Hardware description

The TOE distinguishes different TOE modes as depicted in the following figure:




Figure 2. TOE modes overview

The Super-System Mode (SSM) executes the Boot Software and Firmware.

The Test Mode (SSM-TM, short TM) and Configuration Mode (SSM-CM, short CM) have extended access rights compared to the Super-System Mode. In TM, the IC Dedicated Test Software is executed. Moreover, the IC Dedicated Test Software is used by NXP to download code related to System Mode or User Mode. A customer has no access to the IC Dedicated Test Software. The Configuration Mode is used to configure the TOE in the boot phase and to apply Post-Delivery Configurations.

After production of the Security IC, every start-up or reset completes with execution of the IC Dedicated Test Software. The test functionality is disabled at the end of the production test. Afterwards, every start-up or reset ends up in System Mode or User Mode, depending on the configuration 'Customer Type' selected by the customer.

The TOE further provides the System Mode (SM) and User Mode (UM) which are available for the IC Embedded Software. If both logical cards A and B are available, each card implements its own SM and UM, which are completely separated from each other. If the NXP System Mode OS is not available (SM customer) the MMU has to be configured by the System Mode User, i.e., via the Security IC Embedded Software.

The System Mode has broader access to the hardware components available to the Security IC Embedded Software. The User Mode has restricted access to the CPU, specific Special Function Registers and the memories depending on the access rights granted by software running in System Mode. The hardware components are controlled by the Security IC Embedded Software via Special Function Registers. A more detailed description of the Software available on and for the TOE is given in [Section 1.4.3.2](#).

The N7121 provides interrupts. Interrupts force a jump to a specific fixed vector address in the ROM or Flash. Any interrupt can therefore be controlled and guided by a specific part of the Security IC Embedded Software. In addition, the TOE provides user calls and system calls. These calls have to be explicitly done by the Security IC Embedded Software via dedicated CPU instructions. A user call starts the execution of related code dedicated to one lower privileged mode (Super System Mode to System Mode or System Mode to User Mode). A system call starts the execution of related code dedicated to one higher privileged mode (User Mode to System Mode or System Mode to Super System Mode).

The Watchdog timer is intended to abort irregular program executions by a time-out mechanism and is enabled and configured by the Security IC Embedded Software.

The TOE incorporates Flash, RAM, and program memory available in ROM. Access control to all three memory can be configured by the Memory Management Unit (MMU). The System Mode OS provides a simplification of the resource management (e.g. MMU firewall settings, dynamic segment setup, and peripheral access control).

The Triple-DES coprocessor supports single DES and Triple-DES operations. Only Triple-DES is in the scope of this evaluation, in 2-key or 3-key configurations, each 56-bit long (e.g., 112-bit or 168-bit key in total). The AES coprocessor supports AES operation with three different key lengths of 128, 192 or 256 bit. Both utilize the new Crypto2+ coprocessor. The physical random number generator provides true random numbers without pseudo random calculation. The new 128 bit Public Key Crypto Coprocessor (Fame3) supplies basic arithmetic functions to support the implementation of asymmetric cryptography, utilized by the asymmetric cryptographic library.

The TOE provides power saving modes with reduced activity. These are named IDLE Mode and SLEEP Mode, of which the latter one includes CLOCK STOP Mode.

The TOE protects secret data, which are stored on and operated by the TOE, against physical tampering. A memory encryption is added to the memories RAM, ROM and Flash such that data stored to these memories is encrypted. Chip shielding is added in form of an active shield. Light sensors are distributed over the chip area. Furthermore, the TOE is protected by voltage, temperature and frequency sensors. The security functionality of the IC hardware platform is mainly provided by the TOE, and completed by the Security IC Embedded Software. This causes dependencies between the security functionality of the TOE and the security functionality provided by the Security IC Embedded Software.

1.4.3.2 Software description




Figure 3. Software components of the TOE

Figure 3 shows the different pieces of the available software on and for the TOE. The scope of the TSF is additionally highlighted by a red box. The TOE supports two logical cards (Card A and Card B). Both logical cards are divided into a User Mode and a System Mode. Operating system and applications of a Security IC are developed by the customers and included under the heading Security IC Embedded Software. The logical location of the Security IC Embedded Software depends on the usage of the IC hardware platform. For User Mode customers, it is stored in the memories which belong to the User Mode of Card B. For System Mode customers, the Security IC Embedded Software can also be stored in memories which belong to the System Mode of Card B. Logical Card A is available for NXP code only. If this logical card is available, the SM of card A contains the NXP SM OS while User Mode of Card A contains NXP code like MIFARE Plus or MIFARE DESFire. The SM of Card A also contains NXP-provided shared libraries that can be made available to code running in logical card B. In case no MIFARE DESFire or MIFARE Plus functionality is ordered by the customer, the memory space of the User Mode in logical card A is set to zero.

The separation between the two logical cards (Card A and Card B) is provided by the so-called "Vertical IP firewall" which allows for having two completely separated logical cards on the same hardware without any unintended impact on each other. Because a logical card is also divided into a User Mode and a System Mode, it is possible to offer a security feature called "Secure User Mode Box".

This feature is of special importance as it allows for the integration of data and code to a certified product without any security impact. The Secure User Mode Box restricts the access rights for code running in UM of Card A, such that it has no influence on other modes and cards. The NXP System Mode OS does not provide any interfaces to the UM to change these access rights.

The TOE architecture allows using shared memory segments to share data or code between the separated logical cards. The libraries are shared between the logical cards using this mechanism, reducing the footprint, as code only has to be present on the device once. An inter-card communication mechanism allows the currently active card to send a message to the inactive card with a request for card switching. This mechanism allows for the handover of execution between the logical cards.

The IC Dedicated Test Software is developed by NXP. It includes the test operating system, test routines for the various blocks of the circuitry, control flags for the status of the Flash's manufacturer area and shutdown functions.

The IC Dedicated Support Software comprises the following parts:

1. The Boot Software is executed after each reset of the TOE, i.e. every time when the TOE starts. It sets up the TOE and does some basic configuration of the hardware based on the settings stored in memories assigned to the SSM.
The Boot Software is stored in ROM memories assigned to the SSM.
2. The Firmware Interface is stored in memories assigned to the SSM. It provides low-level flash management, the Post-Delivery Configuration feature and basic system functionality like self-testing, error-counter handling, PUF and reset functionality. Notice, that Boot Software and IC Dedicated Test Software also access the Firmware Interface. The 'one-time executed' part of the Firmware Interface (for instance PDC) is located in FLASH, the remaining parts are located in ROM.
3. The NXP System Mode OS is an Operating System developed by NXP. In general, the NXP System Mode OS provides a ready-to-use resource and access management for any customer application and does not expose the more low-level features, such as MMU configuration. It provides the feature of the Secure User-Mode Box.
The NXP System Mode OS is a mandatory component of Card A, implementing its System Mode OS. It is responsible for sharing the different TOE libraries available. For System Mode customers who do not need any TOE library, the Flash Loader, or any NXP application running in User Mode of Card A, the System Mode OS on Card A is deactivated and cannot be executed. This results in the deactivation of Card A. For Card B the NXP System Mode OS is an optional component. However, it becomes mandatory for User Mode customers.
The NXP System Mode OS can be stored in ROM or FLASH.
4. The Library Interface module is stored in the shared memory segment in System Mode of Card A. It provides simplified communication, CRC and memory functions to the Security IC Embedded Software. The Library Interface is required by the Flashloader OS and the Crypto Libraries.
5. The crypto library is an optional library which provides extended functionality and access to the following functionality to the Security IC Embedded Software:
 - Package Symmetric Ciphers for AES and TDES in various modes.
 - Package Random Number Generation which implements the hybrid deterministic RNG and hybrid physical RNG including health tests.
 - Package RSA Encryption / Decryption: RSA encryption, decryption and signature generation with key sizes from 1976 and up to 4096 bits. Key sizes from 512 bits and less than 1976 bits are also supported but not in the scope of evaluation.
 - Package RSA Key Generation: Generation of RSA key pairs and public key computation with key sizes from 1976 and up to 4096 bits. If FIPS compliance is

enforced, only key sizes from 2048 to 3072 bits are supported. Key sizes from 512 bits and less than 1976 bits are also supported but not in the scope of evaluation.

- Package ECC over GF(p):
 - The ECDSA (ECC over GF(p)) algorithm can be used for signature generation and signature verification.
 - The ECDSA (ECC over GF(p)) key generation algorithm can be used to generate ECC over GF(p) key pairs for ECDSA.
 - The ECDH (ECC Diffie-Hellman) key exchange algorithm can be used to establish cryptographic keys. For the release package R1, R2 and R3, it can be also used as secure point multiplication for curves with key sizes 256, 384 and 512 bits. The key size limitation does not apply for the release package R4.
 - Provide secure point addition for Elliptic Curves over GF(p).
 - Provide curve parameter verification for Elliptic Curves over GF(p).
 - The TOE supports various key sizes for ECC over GF(p) up to a limit of 640 bits for signature generation, key pair generation and key exchange. For signature verification the TOE supports key sizes up to a limit of 640 bits.
- Package SHA:
 - The SHA-1, SHA-224, SHA-256, SHA-384, and SHA-512 algorithms can be used for different purposes such as compute hash values in the course of digital signature creation and key verification.
- The crypto library implements the KeyStore feature for a secure key management in RAM.
- The crypto library further implements secure move, copy, and compare operations. Even though the TOE does not implement the full PACE protocol, the release package R4 of the TOE provides basic support for the implementation of this protocol in the IC Embedded Software via these secure operations.

6. The Flashloader OS is an optional module and stored in memory segments assigned to SM of Logical Card B. It is located in ROM and FLASH. One-time executed code is located in FLASH and is removed after use. The freed up memory is then available for the Security IC Embedded Software.

The Flashloader OS supports the download of code and data to Flash by the Composite Product Manufacturer before Operational Usage (e.g. during development). This functionality shall be permanently disabled before delivery to the end-user in life-cycle Phase 7. When the Flashloader OS module is available, the Library Interface, the N7121 Crypto Library and the System Mode OS become mandatory. All logical dependencies of the IC Dedicated Support Software are described in the definitions above.

Note: Both cryptographic libraries are provided as a library rather than as a monolithic program, and hence a user of the library may include only those functions that are actually required – it is not necessary to include all cryptographic functions of the library in every Security IC Embedded Software. For this purpose, [Table 4](#) defines different packages of the crypto libraries which can be included in the customer application. For example, it is possible to use the package ECC over GF(p) only in case of the N7121 Crypto Library. The inter-dependencies of the different packages are resolved in [Table 4](#).

With respect to Application note 32 of the [\[PP\]](#), the physical location of the Security IC Embedded Software can be either in ROM or in Flash. The Security IC Embedded Software itself is not in the scope of this evaluation.

All logical dependencies of the IC Dedicated Support Software are described in the definitions above.

1.4.4 Security during Development and Production

The Security IC product life-cycle is scheduled in phases as introduced in [PP]. IC Development as well as IC Manufacturing and Testing, which are Phases 2 and 3 of the life-cycle, are part of the evaluation. Phase 4 the IC Packaging is also part of the evaluation. The Security IC is delivered at the end of Phase 3 or Phase 4 in the life-cycle (Application Note 1 of [PP]). The development and production environment of the TOE ranges from Phase 2 to TOE Delivery.

With respect to Application Note 3 in [PP] the TOE supports the authentic delivery using the FabKey feature. For further details refer to the data sheet [DSheet] and the guidance and operation manual [GOM].

During the design and the layout process only personnel involved in the specific development project for an IC have access to sensitive data. Different teams are responsible for the design data and for customer related data. The test process of every die is performed in CC certified test centers. Delivery processes between the involved sites provide accountability and traceability of the TOE. The TOE is provided in form of sawn wafers, modules, inlays or packages depending on the individual commercial type.

1.4.5 TOE intended usage

The end-consumer environment of the TOE is Phase 7 of the Security IC product life-cycle as defined in [PP]. In this phase the Security IC product is in usage by the end-consumer. Its method of use now depends on the Security IC Embedded Software. The Security ICs including the TOE can be used to perform various functions in a wide range of applications. Examples are identity cards, Banking Cards, Pay-TV, Health cards and Transportation cards. The end-user environment covers a wide spectrum of very different functions, thus making it difficult to monitor and avoid abuse of the TOE. The TOE is intended to be used in an insecure environment, which does not protect against threats.

The device is developed for high-end safeguarded applications, and is designed to be suited for embedding into chip cards with various possible communication interfaces, for example ISO/IEC 7816, contactless applications according to ISO/IEC 14443 or others. Usually a Security IC (e.g. a smartcard) is assigned to a single individual only, but it may also be used by multiple applications in a multi-provider environment. Therefore the TOE might store and process secrets of several systems, which must be protected from each other. The TOE then must meet security requirements for each single security module.

Secret data shall be used as input for calculation of authentication data, calculation of signatures and encryption of data and keys.

The user environment of the TOE ranges from TOE delivery to Phase 7 of the Security IC product life-cycle, and must be a controlled environment up to Phase 6.

Note: *The TOE can be delivered as a stand-alone security IC with deactivated GPIO interface or as a certified component of a product that contains a sidecar connecting to the TOE's interface wirings. If GIPO is available as an external interface of the TOE, no security relevant data must be processed, or must be protected by means that is outside the scope of the TOE. In case the GPIO is deactivated, the deactivation mechanism is protected by physical countermeasures like shielding, redundancy and sensors.*

Note: *Please note that the phases from TOE Delivery to Phase 7 of the Security IC Product life-cycle are not part of the TOE construction process in the sense of this Security Target. Information about these phases is just included to describe how the TOE is used after its construction. Nevertheless such security functionality of the TOE, that is*

independent of the Security IC Embedded Software, is active at TOE Delivery and cannot be disabled by the Security IC Embedded Software in the following phases.

Note: *Additionally, it is important to note that, the integration of the TOE, that is the hard macro, resulting in the final product is done within the premise of NXP and inside its secure IT environment only.*

Note: *Finally, any side-car which is potentially developed outside of the NXP's secure development network must be merged with the hardmacro inside NXP's secure development network. The hardmacro design details of the hardmacro will not be provided to any external party.*

1.4.6 Interface of the TOE

The electrical interface of the N7121 are the pads to connect the lines power supply, ground, reset input and clock input. The TOE provides a general purpose I/O interface which allows direct access to the internal SFR bus. This is an external interface that can be used to connect an I2C interface for instance without affecting the certification.

The TOE implements conventional contact-based and contactless interfaces (ISO/IEC 7816 contact interface with UART and ISO/IEC 14443A contactless interface). The availability of these interfaces depends on the actual configuration of the TOE.

The logical interface of the TOE depends on the CPU mode and the associated software.

- Upon every start-up the Boot Software is executed in Super System Mode. This software initializes and configures the TOE. This comprises the selection of IC Dedicated Test Software (before TOE delivery) and of Security IC Embedded Software (after TOE delivery). Only in case the configuration option 'Enable Chip Health Mode' is enabled, starting of built-in self-test routines and read-out of TOE identification items is supported. If this configuration option is disabled, the Boot Software provides no interface.
- Before TOE delivery the logical interface is defined by the IC Dedicated Test Software. This IC Dedicated Test Software is executed in Super System Mode and comprises the test operating system used for production testing. IC Dedicated Test Software is embedded in the Test Software.
- In System Mode and User Mode (after TOE Delivery) the software interface is the set of instructions, the bits in the special function registers that are related to these modes and the physical address map of the CPU including memories. The access to the special function registers as well as to the memories depends on the TOE mode configured by the Security IC Embedded Software.

Note: *The logical interface of the TOE that is visible on the electrical interface after TOE Delivery is based on the Security IC Embedded Software developed by the software developer. The identification and authentication of the user in System Mode or User Mode must be controlled by the Security IC Embedded Software.*

Note: *The chip surface can be seen as an interface of the TOE, too. This interface must be taken into account regarding environmental stress e.g. like temperature and in the case of an attack, for which the attacker manipulates the chip surface.*

Note: *An external voltage and timing supply as well as a logical interface are necessary for the operation of the TOE. Beyond the physical behavior of the logical interface is defined by the Security IC Embedded Software.*

2 Conformance claims

This Security Target claims to be conformant to the Common Criteria version 3.1:

- *Common Criteria, Part 1: Common Criteria for Information Technology Security Evaluation, Part 1: Introduction and general model*, Version 3.1, Revision 5, April 2017, CCMB-2017-04-001. [\[CC_Part1\]](#)
- *Common Criteria, Part 2: Common Criteria for Information Technology Security Evaluation, Part 2: Security functional components*, Version 3.1, Revision 5, April 2017, CCMB-2017-04-002. [\[CC_Part2\]](#)
- *Common Criteria, Part 3: Common Criteria for Information Technology Security Evaluation, Part 3: Security assurance components*, Version 3.1, Revision 5, April 2017, CCMB-2017-04-003. [\[CC_Part3\]](#)

For the evaluation the following methodology will be used:

- *Common Methodology for Information Technology Security Evaluation, Evaluation Methodology*, Version 3.1, Revision 5, April 2017, CCMB-2017-04-004. [\[CEM\]](#)

This Security Target claims to be **CC Part 2 extended** and **CC Part 3 conformant**. The extended Security Functional Requirements are defined in [Section 5](#).

2.1 Package claim

This Security Target claims conformance to the assurance package EAL6 augmented. The augmentations to EAL6 is ALC_FLR.1. In addition, the Security Target is augmented using the component ASE_TSS.2, which is chosen to include architectural information on the security functionality of the TOE.

The level of evaluation and the functionality of the TOE are chosen in order to allow the confirmation that the TOE is suitable for use within devices compliant with the German Digital Signature Law.

Note: *The Protection Profile (PP) "Security IC Platform Protection Profile with Augmentation Packages" [\[PP\]](#) to which this Security Target claims conformance (refer to [Section 2.2](#)) requires assurance level EAL4 augmented. The changes, which are needed for EAL6, are described in the relevant sections of this Security Target.*

2.2 PP claim

This Security Target claims strict conformance to the Protection Profile (PP):

- *Security IC Platform Protection Profile with Augmentation Packages*, Version 1.0, registered and certified by Bundesamt für Sicherheit in der Informationstechnik (BSI) under the reference BSI-PP-0084-2014 [\[PP\]](#).

Thus, the concepts are used in the same sense. For the definition of terms refer to [\[PP\]](#). This chapter does not need any supplement in the Security Target.

This conformance claim includes the following packages of security requirements out of those for Loader defined in the Protection Profile:

- Package "Package 1: Loader dedicated usage in Secured Environment only" Conformant and
- Package "Package2: Loader dedicated for usage by authorized users only" Conformant.

This conformance claim includes the following packages of security requirements out of those for Cryptographic Services defined in the Protection Profile [\[PP\]](#):

- Package "TDES" Conformant and
- Package "AES" Conformant.

If the respective package of the crypto library is available, the additional functionality results in the following change to the conformance claim:

- Package "TDES" Augmented and
- Package "AES" Augmented.

Furthermore, if the respective package of the crypto library is available, the additional functionality results in the inclusion of the following conformance claim:

- Package "Hash functions" Conformant.

The TOE provides additional functionality, which is not covered in [\[PP\]](#). In accordance with Application Note 4 of [\[PP\]](#) this additional functionality is added using the policy P.Add-Components and P.Add-Crypto-Func (see [Section 3.3](#)).

2.3 Conformance claim rationale

According to [Section 2.2](#) this ST claims strict conformance to [\[PP\]](#).

The TOE type defined in [Section 1.3.5](#) is a smartcard controller with IC Dedicated Software. This is consistent with the TOE definition for a Security IC in Section 1.2.2 of [\[PP\]](#). The sections within this document where Security Problem Definitions, Security Objectives and Security Functional Requirements (SFR) are defined, clearly state which of these items are taken from the Protection Profile and which are added in this Security Target. Moreover, all additionally stated items in this Security Target do not contradict the items included from the PP (see the respective sections in this document). The operations done for the SFRs taken from the PP are also clearly indicated.

The evaluation assurance level claimed for this TOE is shown in [Section 6.2](#) to include respectively exceed the requirements claimed by the PP (EAL4+).

These considerations show that the Security Target correctly claims conformance to [\[PP\]](#).

3 Security problem definition

This chapter lists the assets, threats, assumptions and organizational security policies from [PP] and describes extensions to these elements in detail.

3.1 Description of assets

All assets, which are defined in Section 3.1 of the [PP], are related to standard functionality. They are applied in this Security Target. These assets are:

- integrity and confidentiality of User Data stored and in operation,
- integrity and confidentiality of Security IC Embedded Software, stored and in operation,
- correct operation of the Security Services provided by the TOE for the Security IC Embedded Software, and
- random numbers.

To be able to protect these assets the TOE shall protect its Security Functionality. Therefore critical information on the TOE shall be protected. Critical information includes:

- logical design data, physical design data, IC Dedicated Software, as well as
- initialization data and pre-personalization data, Security IC Embedded Software, specific development aids, test and characterization related data, material for software development support, and photo masks.

Note: Note that the keys for cryptographic calculations using security services of the TOE are treated as User Data.

3.2 Threats

The Threats defined in Protection Profile are used for this ST without change. Therefore, see [PP] for their definitions. A complete list of Threats defined in [PP] is given in the following table:

Table 8. Threats defined in Protection Profile

Name	Title
T.Leak-Inherent	Inherent Information Leakage
T.Phys-Probing	Physical Probing
T.Malfunction	Malfunction due to Environmental Stress
T.Phys-Manipulation	Physical Manipulation
T.Leak-Forced	Forced Information Leakage
T.Abuse-Func	Abuse of Functionality
T.RND	Deficiency of Random Numbers

The following additional threats are defined in this Security Target:

Table 9. Additional threats defined in this Security Target

Name	Title
T.Mem-Access	Memory Access Violation
T.Malicious-UM-Application	Malicious code running in UM of Card A (optional)

T.Mem-Access

Memory Access Violation

Parts of the Security IC Embedded Software may cause security violations by accidentally or deliberately accessing restricted data (which may include code). Any restrictions are defined by the security policy of the specific application context and must be implemented by the Security IC Embedded Software.

Note:Restricted data can include special function registers that control hardware peripherals.

T.Malicious-UM-Application

Malicious code running in UM of Card A (optional)

An attacker may try to use malicious code placed in User Mode of logical card A to modify the correct behavior of the Security IC Dedicated Software or the Security IC Embedded Software as well as read or modify code or data belonging to the Security IC Dedicated Software or the Security IC Embedded Software. This threat is only applicable if the logical card A is available.

3.3 Organizational security policies

The Security Policies defined in [PP] are used for this ST without change. Therefore, see [PP] for their definitions. A complete list of Threats defined in [PP] is given in the following table:

Table 10. Security policies defined in the Protection Profile

Name	Title
P.Process-TOE	Identification during TOE Development and Production
P.Lim_Block_Loader	Limiting and Blocking the Loader Functionality
P.Ctrl_Loader	Controlled usage to Loader Functionality
P.Crypto-Service	Cryptographic services of the TOE

In compliance with Application Note 5 in the [PP], this Security Target defines additional security policies as detailed below.

The TOE provides specific security functionality, which can be used by the Security IC Embedded Software. This specific security functionality is not derived from threats identified for the TOE. Instead, the Security IC Embedded Software decides how to use this security functionality to protect from threats for the composite product. Thus, security policy P.Add-Components is defined as follows.

P.Add-Components

Additional Specific Security Components

The TOE shall provide the following additional security functionality to the Security IC Embedded Software:

- self-tests, and
- integrity support of data stored to NVM.

P.Add-Crypto-Func

Additional Cryptographic Functionality (optional)

The TOE shall provide the following additional cryptographic functionality to the Security IC Embedded Software:

- PUF functionality,
- RSA encryption, decryption, signature generation, signature verification, message encoding and signature encoding,
- RSA public key computation,
- RSA key generation,
- ECDSA (ECC over GF(p)) signature generation and verification,
- ECC over GF(p) key generation,
- ECDH (ECC Diffie-Hellmann) key exchange,
- ECC over GF(p) point addition,
- ECC over GF(p) curve parameter verification.

Note: This policy depends on the TOE configuration and the availability of the N7121 Crypto Library.

3.4 Assumptions

All assumptions defined in Section 3.4 of [PP] are valid for this Security Target:

Table 11. Assumptions defined in the Protection Profile

Name	Title
A.Process-Sec-IC	Protection during Packaging, Finishing and Personalisation
A.Resp-Appl	Treatment of user data of the Composite TOE

In compliance with Application Notes 6 and 7 of [PP], this Security Target defines two additional assumptions as follows.

A.Check-Init

Check of initialization data by the Security IC Embedded

The Security IC Embedded Software must provide a function to check initialization data. Such data is defined by the Composite Product Manufacturer and injected by the TOE Manufacturer into the non-volatile memory to provide the ability to identify and trace the TOE.

A.Key-Function

Usage of Key-dependent Functions

Key-dependent functions (if any) shall be implemented in the Security IC Embedded Software in a way that they are not susceptible to leakage attacks (as described under T.Leak-Inherent and T.Leak-Forced).

Note: Note that here the routines which may compromise keys when being executed are part of the Security IC Embedded Software. In contrast to this the threats T.Leak-Inherent and T.Leak-Forced address (i)

*the cryptographic routines which are part of the TOE and
(ii) the processing of User Data including cryptographic
keys.*

4 Security objectives

4.1 Security objectives of the TOE

All Security Objectives of the TOE, which are defined in [PP] are applied to this Security Target. This also comprises the Security Objectives defined in the functional packages which are claimed in [Section 2.2](#). The following table lists these Security Objectives of the TOE:

Table 12. Security objectives of the TOE defined in the Protection Profile

Name	Title
O.Leak-Inherent	Protection against Inherent Information Leakage
O.Phys-Probing	Protection against Physical Probing
O.Malfunction	Protection against Malfunctions
O.Phys-Manipulation	Protection against Physical Manipulation
O.Leak-Forced	Protection against Forced Information Leakage
O.Abuse-Func	Protection against Abuse of Functionality
O.Identification	TOE Identification
O.RND	Random Numbers
O.Cap_Avail_Loader	Capability and availability of the Loader
O.Ctrl_Auth_Loader (optional)	Access control and authenticity for the Loader
O.TDES	Cryptographic service Triple-DES
O.AES	Cryptographic service AES
O.SHA (optional)	Cryptographic service Hash functions

The objective O.Ctrl_Auth_Loader depends on the current state of the Flash Loader. In case the Flash Loader is blocked (after usage or as the Flash Loader is deactivated following [Table 3](#)), the respective functionality is not available anymore. The objectives O.AES and O.TDES depend on the availability of the AES and DES coprocessor which can be deactivated following [Table 3](#).

In compliance with Application Notes 8 and 9 of [PP], additional Security Objectives for the TOE are defined below based on additional functionality provided by the TOE.

O.NVM-Integrity

Integrity Support of data stored to NVM

The TOE shall provide detection and correction of failures in NVM memories to support integrity of contents stored there.

O.Mem-Access

Area based Memory Access Control

The TOE must provide the Security IC Embedded Software with the capability to define restricted access memory areas. The TOE must then enforce the partitioning of such memory areas so that access of software to memory areas is controlled as required, for example, in a multi-application environment.

Note: Restricted memory areas includes special function registers that control hardware peripherals.

O.Self-Test

Self-Test

The TOE shall include functionality to perform a self-test to detect physical manipulation.

O.PUF (optional)

Sealing/Unsealing user data

The TOE shall provide PUF functionality that supports sealing/unsealing of User Data. Using this functionality, the User Data can be sealed within the TOE and can only be unsealed by the same TOE that the User Data was sealed on. The PUF functionality comprises import/export of data, encryption/decryption of data and calculation of a MAC as a PUF authentication value.

Note: The PUF functionality provided by the TOE shall only be active if explicitly configured by the Security IC Embedded Software.

Note: This objective requires the availability of the PUF which can be deactivated depending on the ordered TOE configuration. Furthermore, encryption and decryption requires the availability of the AES coprocessor which can be deactivated via Post-Delivery Configuration.

O.Secure-User-Mode-Box (optional)

Secure User Mode Box Firewall

The TOE shall provide specific separation between the Secure UM Box code and other parts of the TOE. The separation shall comprise software execution and data access.

Note: This objective is only applicable if the customer ordered an NXP application running in User Mode of logical card A and relies on the NXP System Mode OS running in System Mode of logical card A.

O.RSA

RSA Functionality (optional)

The TOE includes functionality to provide encryption, decryption, signature creation, signature verification, message encoding and signature encoding using the RSA algorithm. Furthermore, the TOE provides functionality to compute a public RSA key from a given private RSA key as well as RSA key-pair generation.

Note: This objective requires the availability of the N7121 Crypto Library.

O.ECC

Elliptic-Curve Cryptography over GF(p) (optional)

The TOE provides signature generation and verification, Diffie-Hellmann key exchange, each using the ECC

over GF(p) algorithm. It further includes functionality to generate ECC over GF(p) key pairs.

Note: This objective requires the availability of the N7121 Crypto Library.

4.2 Security objectives of the security IC embedded software development

All security objectives for the Security IC Embedded Software development Environment, which are defined in [PP], are applied to this Security Target.

Table 13. Security Objectives of the Security IC Embedded Software Development defined in Protection Profile

Name	Title
OE.Resp-Appl	Treatment of User Data

Clarification related to OE.Resp-Appl:

By definition cipher or plain text data and cryptographic keys are User Data. The Security IC Embedded Software shall treat these data appropriately, use only proper secret keys (chosen from a large key space) as input for the cryptographic function of the TOE and use keys and functions appropriately in order to ensure the strength of cryptographic operation. This means that keys are treated as confidential as soon as they are generated. The keys must be unique with a very high probability, as well as cryptographically strong. If keys are imported into the TOE and/or derived from other keys, quality and confidentiality must be maintained. This implies that appropriate key management has to be realized in the environment.

In case the Security IC Embedded Software operates multiple applications on the TOE, OE.Resp-Appl must also be met. The Security IC Embedded Software must not disclose security relevant User Data of one application to another application when processed in or stored to the TOE.

4.3 Security objectives for the Operational Environment

All Security Objectives for the Operational Environment of the TOE, which are defined in [PP] are applied to this Security Target. This also comprises the Security Objectives for the Operational Environment defined in the functional packages which are claimed in [Section 2.2](#). The following table lists these Security Objectives of the TOE:

Table 14. Security objectives for the Operational Environment

Name	Title
OE.Process-Sec-IC	Protection during composite product manufacturing
OE.Lim_Block_Loader	Limitation of capability and blocking the Loader
OE.Loader_Usage (optional)	Secure communication and usage of the Loader

The following additional security objectives for the operational environment are defined in this Security Target.

The following security objective for the operational environment derives from assumption A.Check-Init. The TOE provides specific functionality that requires the TOE Manufacturer

to implement measures for unique identification of the TOE. Security objective OE.Check-Init is defined to allow for such a TOE specific implementation.

OE.Check-Init

Check of initialization data by the Security IC Embedded Software

To ensure the receipt of the correct TOE, the Security IC Embedded Software shall check a sufficient part of the pre-personalization data. This shall include at least the FabKey data that is agreed between the customer and the TOE Manufacturer.

4.4 Security objectives rationale

Section 4.4 of [PP] provides a rationale how the threats, organisational security policies and assumptions are addressed by the Security Objectives defined in [PP]. The following table summarizes how Threats, Organizational Security Policies and Assumptions defined in this ST in extension to [PP] are addressed by Security Objectives defined in the PP and ST, respectively.

Table 15. Security Objectives (PP and ST) vs. Security Problem Definition (PP and ST)

Security Problem Definition	Security Objective	Note
T.Leak-Inherent	O.Leak-Inherent	--
T.Phys-Probing	O.Phys-Probing	--
T.Malfunction	O.Malfunction O.Self-Test	--
T.Phys-Manipulation	O.Phys-Manipulation O.Self-Test	--
T.Leak-Forced	O.Leak-Forced	--
T.Abuse-Func	O.Abuse-Func	--
T.RND	O.RND	--
P.Process-TOE	O.Identification	Phases 2–3
A.Process-Sec-IC	OE.Process-Sec-IC	Phases 4–6
A.Resp-Appl	OE.Resp-Appl	Phase 1
P.Lim_Block_Loader	O.Cap_Avail_Loader OE.Lim_Block_Loader	--
P.Ctrl_Loader	O.Ctrl_Auth_Loader OE.Loader_Usage	--
P.Crypto-Service	O.TDES O.AES O.SHA	--
T.Mem-Access	O.Mem-Access	--
T.Malicious-UM-Application (optional)	O.Secure-User-Mode-Box (optional)	--

Table 15. Security Objectives (PP and ST) vs. Security Problem Definition (PP and ST)...*continued*

Security Problem Definition	Security Objective	Note
P.Add-Components	O.Self-Test O.NVM_Integrity	--
P.Add-Crypto-Func (optional)	O.PUF (optional) O.RSA (optional) O.ECC (optional)	--
A.Check-Init	OE.Check-Init	--
A.Key-Function	OE.Resp-Appl	--

In the table above, bold text is used to indicate threats, OSPs, assumptions, and objectives which are added to this ST in extension to the PP.

The following table provides rationales for the assignments of Security Objectives to Threats, and Policies which are not already provided in [PP].

Table 16. Rationales for the assignments between the Security problem definition and the Security objectives not already covered in the Protection Profile

Security problem definition	Security objective	Rationale
T.Malfunction	O.Self-Test	This objective requires that the TOE provides self-testing features for security critical components, thus contributing to cover this threat.
T.Phys-Manipulation	O.Self-Test	This objectives requires that the TOE provides self-testing features for security critical components, thus contributing to cover this threat.
T.Mem-Access	O.Mem-Access	According to O.Mem-Access the TOE must enforce the partitioning of memory areas so that access of software to memory areas and/or hardware special function registers is controlled. Any restrictions are to be defined by the Security IC Embedded Software. Thereby security violations caused by accidental or deliberate access to restricted data (which may include code) or hardware resources can be prevented (refer to T.Mem-Access). The threat T.Mem-Access is therefore removed if the objective is met.
T.Malicious-UM-Application (optional)	O.Secure-User-Mode-Box (optional)	This objectives enforces the Secure User-Mode Box, thus contributing to cover this threat.
P.Add-Components	O.Self-Test	This objective covers the security policy because it requires the TOE to partly implement the functionality as required by the security policy.
	O.NVM-Integrity	This objective covers the security policy because it requires the TOE to partly implement the functionality as required by the security policy.
P.Add-Crypto-Func (optional)	O.PUF (optional)	This objective covers the security policy because it requires the TOE to partly implement the functionality as required by the security policy.

Table 16. Rationales for the assignments between the Security problem definition and the Security objectives not already covered in the Protection Profile...continued

Security problem definition	Security objective	Rationale
	O.RSA (optional)	This objective covers the security policy because it requires the TOE to partly implement the functionality as required by the security policy.
	O.ECC (optional)	This objective covers the security policy because it requires the TOE to partly implement the functionality as required by the security policy.
A.Check-Init	OE.Check-Init	This objective requires the Security IC Embedded Software developer to implement a function as stated in this assumption.
A.Key-Function	OE.Resp-Appl	The definition of this objective of the [PP] is further clarified in this Security Target: By definition cipher or plain text data and cryptographic keys are User Data. So, the Security IC Embedded Software will protect such data if required and use keys and functions appropriately in order to ensure the strength of cryptographic operation. Quality and confidentiality must be maintained for keys that are imported and/or derived from other keys. This implies that appropriate key management has to be implemented in the environment. In addition, the treatment of User Data comprises the implementation of a multi-application operating system that does not disclose security relevant User Data of one application to another one. These measures make sure that the assumption A.Key-Function is still covered by this objective.

The justification of the additional policy and the additional assumptions show that they do not contradict to the rationale already given in the Protection Profile for the assumptions, policy and threats defined there.

5 Extended components definition

The underlying Protection Profile [PP] contains extended components. This Security Target defines further extended components described below.

5.1 Cryptographic Key Derivation (FCS_CKM.5)

FCS_CKM.5 Cryptographic Key Derivation requires the TOE to provide key derivation which can be based on an assigned standard.

FCS_CKM.5	Cryptographic Key Derivation
Hierarchical to:	No other components
Dependencies:	[FCS_CKM.2 Cryptographic Key Distribution, or FCS_COP.1 Cryptographic Operation] FCS_CKM.4 Cryptographic Key Destruction
FCS_CKM.5.1	The TSF shall derive cryptographic keys [assignment: <i>key type</i>] from [assignment: <i>input parameters</i>] in accordance with a specified cryptographic key derivation algorithm [assignment: <i>cryptographic key derivation algorithm</i>] and specified cryptographic key sizes [assignment: <i>cryptographic key sizes</i>] that meet the following: [assignment: <i>list of standards</i>].
Application Notes:	None

6 Security requirements

This chapter defines the security requirements that shall be met by the TOE. These security requirements are composed of the Security Functional Requirements (SFR) and the Security Assurance Requirements (SAR) that the TOE must meet in order to achieve its security objectives. CC allows several operations to be performed on security requirements (on the component level); refinement, selection, assignment, and iteration are defined in Section 8.1 of [CC_Part1]. These operations are used in the [PP] and in this Security Target, respectively.

- The refinement operation is used to add details to requirements, and thus, further intensifies a requirement. Refinements are indicated as **bold text**.
- The selection operation is used to select one or more options provided by the PP or CC in stating a requirement. Selections having been made are denoted as *italic text*.
- The assignment operation is used to assign a specific value to an unspecified parameter, such as the length of a password. Assignments having been made are denoted as underlined text.
- The ST applies further refinements by deleting specific words. These refinements are indicated by _{subscript text}. These refinements do not affect the meaning of the SFRs and are only applied for grammatical reasons.
- The iteration operation is used when a component is repeated with varying operations. It is denoted by the same notation used in [PP], i.e., a slash followed by the iteration indicator. Whenever an element in [PP] contains an operation that is left uncompleted, the Security Target has to complete that operation.

Note: Please note that this ST does not indicate the operations already performed in [PP]. Therefore, this ST only highlights those operations which are left open in the [PP]. If an SFR was not taken from the certified PP but from CC Part 2, the ST identifies all operations required by [CC_Part2].

Furthermore, the following sections provide application notes for each SFR as an informative text. These notes are used to indicate the dependency of each SFR to the configuration of the TOE.

6.1 Security functional requirements

All Security Functional Requirements (SFRs) of the TOE are presented in the following sections to support a better understanding of the combination of the PP and this Security Target. With respect to Application Note 12 in [PP], it is clearly stated, which subset of SFRs is taken from the underlying protection profile or its functional packages and which are newly introduced.

6.1.1 Security Functional Requirements of the PP

FRU_FLT.2

Limited fault tolerance

FRU_FLT.2.1

The TSF shall ensure the operation of all the TOE's capabilities when the following failures occur: exposure to operating conditions which are not detected according to the requirement Failure with preservation of secure state (FPT_FLS.1).

Application Note:

The term "failure" above means "circumstances". The TOE prevents failures for the "circumstances" defined above (refinement from [PP]). With respect to Application Notes 15 in [PP], generation of additional audit data is not defined.

This SFR is in place for each TOE configuration.

FPT_FLS.1

Failure with preservation of secure state

FPT_FLS.1.1

The TSF shall preserve a secure state when the following types of failures occur: exposure to operating conditions which may not be tolerated according to the requirement Limited fault tolerance (FRU_FLT.2) and where therefore a malfunction could occur.

Application Note:

The term "failure" above also covers "circumstances". The TOE prevents failures for the "circumstances" defined above (refinement from [PP]). With respect to Application Note 15 in [PP], generation of additional audit data is not defined.

This SFR is in place for each TOE configuration.

FMT_LIM.1

Limited capabilities

FMT_LIM.1.1

The TSF shall be designed and implemented in a manner that limits their capabilities so that in conjunction with "Limited availability (FMT_LIM.2)" the following policy is enforced: Deploying Test Features after TOE Delivery does not allow user data of the Composite TOE to be disclosed or manipulated, TSF data to be disclosed or manipulated, software to be reconstructed and no substantial information about construction of TSF to be gathered which may enable other attacks.

Application Note:

This SFR is in place for each TOE configuration.

FMT_LIM.2

Limited availability

FMT_LIM.2.1

The TSF shall be designed and implemented in a manner that limits their availability so that in conjunction with "Limited capabilities (FMT_LIM.1)" the following policy is enforced: Deploying Test Features after TOE Delivery does not allow user data of the Composite TOE to be disclosed or manipulated, TSF data to be disclosed or manipulated, software to be reconstructed and no substantial information about construction of TSF to be gathered which may enable other attacks.

Application Note:

This SFR is in place for each TOE configuration.

FAU_SAS.1**Audit storage****FAU_SAS.1.1**

The TSF shall provide the test process before TOE Delivery with the capability to store the *Initialisation Data, Pre-personalisation Data and customer-specific Data* in the *Flash*.

Application Note:

With respect to the Application Notes 16 and 17 of [PP], the TOE provides the necessary data for identification and the SFR states the storage location.

This SFR is in place for each TOE configuration.

FDP_SDC.1**Stored data confidentiality****FDP_SDC.1.1**

The TSF shall ensure the confidentiality of the information of the user data while it is stored in *the ROM, RAM and Non-Volatile Memory*.

Application Note:

This SFR is in place for each TOE configuration.

FDP_SDI.2**Stored data integrity monitoring and action****FDP_SDI.2.1**

The TSF shall monitor user data stored in containers controlled by the TSF for *modification, deletion, repetition or loss of data* on all objects, based on the following attributes: *integrity check information associated with the data stored in memories*.

FDP_SDI.2.2

Upon detection of a data integrity error, the TSF shall *perform an error correction if possible and a Security Reset if not*.

Application Note:

With respect to the Application Notes 18 of the [PP], the necessary operations were performed.

This SFR is in place for each TOE configuration.

FPT_PHP.3**Resistance to physical attack****FPT_PHP.3.1**

The TSF shall resist physical manipulation and physical probing to the TSF by responding automatically such that the SFRs are always enforced.

Application Note:

The TSF will implement appropriate mechanisms to continuously counter physical manipulation and physical probing. Due to the nature of these attacks (especially manipulation) the TSF cannot detect attacks on all of its elements. Therefore, permanent protection against these attacks is required ensuring that security functional requirements are enforced. Hence, "automatic response" means here (i) assuming that there might be an attack at

any time and (ii) countermeasures are provided at any time (refinement from [PP]).

This SFR is in place for each TOE configuration.

FDP_ITT.1

Basic internal transfer protection

FDP_ITT.1.1

The TSF shall enforce the Data Processing Policy to prevent the disclosure of user data when it is transmitted between physically-separated parts of the TOE.

Application Note:

The different memories, the CPU and other functional units of the TOE (e.g. a cryptographic co-processor) are seen as physically-separated parts of the TOE.

This SFR is in place for each TOE configuration.

FPT_ITT.1

Basic internal TSF data transfer protection

FPT_ITT.1.1

The TSF shall protect TSF data from disclosure when it is transmitted between separate parts of the TOE.

Application Note:

The different memories, the CPU and other functional units of the TOE (e.g. a cryptographic co-processor) are seen as separated parts of the TOE (see [PP]).

This SFR is in place for each TOE configuration.

FDP_IFC.1

Subset information flow control

FDP_IFC.1.1

The TSF shall enforce the Data Processing Policy on all confidential data when they are processed or transferred by the TOE or by the Security IC Embedded Software.

Application Note:

The different memories, the CPU and other functional units of the TOE (e.g. a cryptographic co-processor) are seen as physically-separated parts of the TOE (see [PP]).

This SFR is in place for each TOE configuration.

FCS_RNG.1/PTG.2

Random number generation – PTG.2

FCS_RNG.1.1/PTG.2

The TSF shall provide a *physical* random number generator that implements:

(PTG.2.1) - A total failure test detects a total failure of entropy source immediately when the RNG has started. When a total failure is detected, no random numbers will be output.

(PTG.2.2) - If a total failure of the entropy source occurs while the RNG is being operated, the RNG prevents the output of any internal random number that depends on

some raw random numbers that have been generated after the total failure of the entropy source.

(PTG.2.3) - The online test shall detect non-tolerable statistical defects of the raw random number sequence (i) immediately when the RNG has started, and (ii) while the RNG is being operated. The TSF must not output any random numbers before the power-up online test has finished successfully or when a defect has been detected.

(PTG.2.4) - The online test procedure shall be effective to detect non-tolerable weaknesses of the random numbers soon.

(PTG.2.5) - The online test procedure checks the quality of the raw random number sequence. It is triggered at regular intervals or continuously. The online test is suitable for detecting non-tolerable statistical defects of the statistical properties of the raw random numbers within an acceptable period of time.

FCS_RNG.1.2/PTG.2

The TSF shall provide octets of bits that meet:

(PTG.2.6) - Test procedure A does not distinguish the internal random numbers from output sequences of an ideal RNG.

(PTG.2.7) - The average Shannon entropy per internal random bit exceeds 0.997.

Application Note:

Application Note 21 in the [PP] refers to for examples for the security capabilities and quality metrics used in some national certification schemes.

The definition of the SFR FCS_RNG.1/PTG.2 was taken from [KS2011], which is identical to the definition found in the [PP], as the TOE is certified in the German Common Criteria scheme.

In accordance with Application Note 44 of the [PP], the assignment for additional standard statistical test suite in clause (PTG.2.6) may be empty.

The Shannon entropy 0.997 per internal random bit compares to 7.976 per octet.

The Shannon entropy is computed as

$$E = - \sum_{i=0}^{255} p_i \log_2 p_i$$

where p_i is the probability that

the byte (b_7, b_6, \dots, b_0) is equal to i as binary number.

The value 7.976 is assigned due to the requirements of [AIS31].

The results of the internal test sequence are provided to the Security IC Embedded Software as a pass or fail criterion.

Application Note:

The N7121 Crypto Library supports statistical test as required in this SFR. The IC Embedded Software has to take care of testing the random numbers generated by the RNG by means of software statistical test. Therefore, this SFR is only partially fulfilled by the hardware TOE. If the Crypto Library is used, the required test functionality is available. In this case, the SFR is completely fulfilled.

6.1.2 Flash Loader (partly optional)

The following table describes the subjects and objects of the Loader policy.

Table 17. Subjects, objects as well as related operations and attributes of the Loader Policy

Identifier	Description
Subjects	
Download User	User Role to download data, verify data and erase data in memory areas.
Key Change User	User Role to update and verify keys.
Developer Mode User	User Role to switch the life cycle to Pre-Release.
Production Mode User	User Role to switch the life cycle to Release.
Self Check User	User Role to perform different sanity checks on the device.
PDC User	User Role to modify PDC values including default OS for each logical card.
Card Operating System	The Card Operating System.
Unauthorized User	An unauthorized user.
Objects as well as related operations and attributes	
Life-Cycle State	<p>Life Cycle State of the Loader.</p> <p>The only available operation is:</p> <ul style="list-style-type: none"> • Switch – Switch from Download to Pre-Release, from Pre-Release to Download or from Download to Release. <p>The available attributes of Life Cycle State are:</p> <ul style="list-style-type: none"> • Download – Initial Life-Cycle State of the TOE which allows download operations. • Pre-Release – Previously downloaded code can be executed. Furthermore, it is possible to return to Life-Cycle State Download. • Release – Final state of the Flash Loader after permanent blocking. No download operations can be performed anymore. It is not possible to switch back to another state of the Life-Cycle State.
Keys	<p>Cryptographic keys used to identify users.</p> <p>The only available operation is:</p> <ul style="list-style-type: none"> • Update – Update or verify a key. <p>The only attribute is:</p> <ul style="list-style-type: none"> • Permissions – Permissions associated with one key to identify subjects.

Table 17. Subjects, objects as well as related operations and attributes of the Loader Policy...continued

Identifier	Description
Memory Segments	<p>Memory segments to which data or code can be downloaded.</p> <p>The available operations are:</p> <ul style="list-style-type: none"> • Download – Download data to a memory segment. • Verify – Verifies the data downloaded to a memory segment. • Erase – Erase data within a memory segment. <p>No attributes available.</p>
User Data	<p>User Data to be stored to, verified in, or removed from Memory Segments.</p> <p>Operations are already covered by the object Memory Segments.</p>

6.1.2.1 Loader Package 1 defined in the PP

FMT_LIM.1/Loader

Limited capabilities – Loader

FMT_LIM.1.1/Loader

The TSF shall be designed and implemented in a manner that limits its capabilities so that in conjunction with "Limited availability (FMT_LIM.2/Loader)" the following policy is enforced

Deploying Loader functionality after *switching to Life Cycle State Release* does not allow stored User Data to be disclosed or manipulated by Unauthorized User.

Application Note:

In Life Cycle State Release, no download operations can be performed anymore. This corresponds to blocking the Flash Loader permanently.

This SFR is in place for each TOE configuration. In case the Flash Loader is not selected in the TOE configuration, its functionality is blocked following this SFR.

FMT_LIM.2/Loader

Limited availability – Loader

FMT_LIM.2.1/Loader

The TSF shall be designed in a manner that limits its availability so that in conjunction with "Limited capabilities (FMT_LIM.1/Loader)" the following policy is enforced

The TSF prevents deploying the Loader functionality after *switching to Life Cycle State Release*.

Application Note:

In Life Cycle State Release, no download operations can be performed anymore. This corresponds to blocking the Flash Loader permanently.

This SFR is in place for each TOE configuration. In case the Flash Loader is not selected in the TOE

configuration, its functionality is blocked following this SFR.

6.1.2.2 Loader Package 2 defined in the PP (optional)

The following SFR depend on the configuration of the TOE. In case the Flash Loader is set to be available, the following SFRs describe the use of the Flash Loader. As soon as the Flash Loader is blocked (which corresponds to the situation when the TOE is configured without Flash Loader), the SFRs of Loader Package 1 address the blocking of the loader functionality.

FTP_ITC.1/Loader

Inter-TSF trusted channel (optional)

FTP_ITC.1.1/Loader

The TSF shall provide a communication channel between itself and *Download User, Key Change User, Developer Mode User and Production Mode User* that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from modification and disclosure.

FTP_ITC.1.2/Loader

The TSF shall permit another trusted IT product to initiate communication via the trusted channel.

FTP_ITC.1.3/Loader

The TSF shall initiate communication via the trusted channel for deploying Loader *functionality as described in FDP_ACF.1/Loader*.

Application Note:

In addition to the required operations, this ST also performs an iteration on this SFR for consistency reasons.

This SFR is in place as long as the Flash Loader is not blocked permanently by setting its Life Cycle State to Release.

FDP_UCT.1/Loader

Basic data exchange confidentiality (optional)

FDP_UCT.1.1/Loader

The TSF shall enforce the Loader SFP to receive User Data in a manner protected from unauthorised disclosure.

Application Note:

In addition to the required operations, this ST also performs an iteration on this SFR for consistency reasons.

This SFR is in place as long as the Flash Loader is not blocked permanently by setting its Life Cycle State to Release.

FDP_UIT.1/Loader

Data exchange integrity (optional)

FDP_UIT.1.1/Loader

The TSF shall enforce the Loader SFP to receive User Data in a manner protected from modification, deletion, insertion errors.

FDP_UIT.1.2/Loader

The TSF shall be able to determine on receipt of User Data, whether modification, deletion, insertion has occurred.

Application Note:

In addition to the required operations, this ST also performs an iteration on this SFR for consistency reasons.

This SFR is in place as long as the Flash Loader is not blocked permanently by setting its Life Cycle State to Release.

FDP_ACC.1/Loader

Subset access control – Loader (optional)

FDP_ACC.1.1/Loader

The TSF shall enforce the *Loader SFP* on:

1. the subjects *Download User, Key Change User, Developer Mode User, Production Mode User, and Card Operating System,*
2. the objects *User Data in memory areas which contain Life Cycle State, Keys and Memory Segments,*
3. the operation deployment of Loader.

Application Note:

The TOE enforces the Loader SFP by FTP_ITC.1/Loader, FDP_UCT.1/Loader, FDP_UIT.1/Loader, and FDP_ACF.1/Loader to describe additional access control rules.

This SFR is in place as long as the Flash Loader is not blocked permanently by setting its Life Cycle State to Release.

FDP_ACF.1/Loader

Security attribute based access control – Loader (optional)

FDP_ACF.1.1/Loader

The TSF shall enforce the Loader SFP to objects based on the following:

1. the subjects *Download User, Key Change User, Developer Mode User, Production Mode User, and Card Operating System* with security attributes: none
2. the objects *User Data in memory areas which contain Life Cycle State, Keys and Memory Segments* with security attributes as listed in [Table 17](#).

FDP_ACF.1.2/Loader

The TSF shall enforce the following rules to determine if an operation among controlled subjects and controlled objects is allowed:

1. *The Developer Mode User is allowed to switch the Life Cycle State from Download to Pre-Release.*
2. *The Production Mode User is allowed to switch the Life Cycle State from Download to Release.*
3. *The Card Operating System is allowed to switch the Life Cycle State from Pre-Release to Download.*

FDP_ACF.1.3/Loader

The TSF shall explicitly authorise access of subjects to objects based on the following additional rules:

1. *The Download User is allowed to Download, Erase, and Verify Memory Segments if Life Cycle State Download grants this right.*
2. *The Key Change User is allowed to update Permissions of Keys if Life Cycle State Download grants this right.*

FDP_ACF.1.4/Loader

The TSF shall explicitly deny access of subjects to objects based on the following additional rules: *as stated in SFR FMT_LIM.2/Loader.*

Application Note:

With respect to Application Note 39 of the [PP], This SFR is in place as long as the Flash Loader is not blocked permanently by setting its Life Cycle State to Release.

6.1.3 Hardware Support for TDES and AES

6.1.3.1 Package TDES defined in PP

The following SFRs address the functionality provided by the TDES coprocessor of the TOE hardware to compute TDES encryption and decryption. With respect to the Functional Package "TDES" of the PP, the functionality provided by the TOE hardware is package conformant.

FCS_COP.1/TDES

Cryptographic operation – TDES

FCS_COP.1.1/TDES

The TSF shall perform *encryption and decryption* in accordance with a specified cryptographic algorithm *TDES in ECB mode* and cryptographic key sizes *168 bits* that meet the following [NIST SP 800-67] Section 3, [NIST SP 800-38A] Section 6.1.

Application Note:

The 2-key (112 bits) Triple-DES operation is supported and in the scope of evaluation even though it has been withdrawn from [NIST SP 800-67].

FCS_CKM.4/TDES**Cryptographic key destruction – TDES****FCS_CKM.4.1/TDES**

The TSF shall destroy cryptographic keys in accordance with a specified cryptographic key destruction method *flushing of key registers* that meets the following: *none*.

6.1.3.2 Package "AES" defined in PP

The following SFRs address the functionality provided by the AES coprocessor of the TOE hardware to compute AES encryption and decryption. With respect to the Functional Package "AES" of the PP, the functionality provided by the TOE hardware is package conformant.

FCS_COP.1/AES**Cryptographic operation – AES****FCS_COP.1.1/AES**

The TSF shall perform *encryption and decryption* in accordance with a specified cryptographic algorithm *AES in ECB mode* and cryptographic key sizes *128 bits, 192 bits, 256 bits* that meet the following: [\[FIPS 197\]](#) Section 5, [\[NIST SP 800-38A\]](#) Section 6.1.

FCS_CKM.4/AES**Cryptographic key destruction – AES****FCS_CKM.4.1/AES**

The TSF shall destroy cryptographic keys in accordance with a specified cryptographic key destruction method *flushing of key registers* that meets the following: *none*.

6.1.4 Further Security Functional Requirements – Cryptographic Library (optional)**6.1.4.1 Library Support for TDES and AES (optional)**

The following SFRs address the functionality provided by the N7121 Crypto Library to compute TDES and AES encryption and decryption. With respect to the Functional Packages "TDES" and "AES" of the PP, the functionality provided by the hardware is package augmented.

Therefore, the following set of SFRs is only available if the N7121 Crypto Library is available. It extends the functionality already provided by the hardware as covered in [Section 6.1.3](#).

FCS_COP.1/TDES_LIB**Cryptographic operation – TDES – Crypto Library (optional)****FCS_COP.1.1/TDES_LIB**

The TSF shall perform *encryption, decryption and MAC generation* in accordance with a specified cryptographic algorithm *TDES in ECB mode, CBC mode, CBC-MAC mode, Retail-MAC mode, and CMAC mode* and cryptographic key sizes *168 bits* that meets the following:

- [\[NIST SP 800-67\]](#) Section 3 (TDES),

- [\[NIST SP 800-38A\]](#) Sections 6.1 and 6.2 (ECB and CBC mode),
- [\[ISO/IEC 9797-1\]](#), Algorithm 1 (CBC-MAC mode),
- [\[ISO/IEC 9797-1\]](#), Algorithm 3 (Retail-MAC mode), and
- [\[NIST SP 800-38B\]](#) Section 6.2 (CMAC mode).

Application Note:

All Triple-DES operations described above are also supported with 112-bit key option. This key option is in the scope of evaluation even though the 112-bit Triple-DES primitive has been withdrawn from [\[NIST SP 800-67\]](#).

This SFR depends on the availability of the N7121 Crypto Library.

FCS_CKM.4/TDES_LIB

Cryptographic Key Destruction – Crypto Library (optional)

FCS_CKM.4.1/TDES_LIB

The TSF shall destroy cryptographic keys in accordance with a specified cryptographic key destruction method *flushing of key registers* that meets the following: *none*.

Application Note:

The N7121 Crypto Library provides the smartcard embedded software with library calls to perform various cryptographic algorithms that involve keys. Through the parameters of the library calls, the smartcard embedded software provides keys for the cryptographic algorithms. To perform its cryptographic algorithms, the library copies these keys, or a transformation thereof, to the working-buffer (supplied by the smartcard embedded software) and/or the memory/special function registers of the Crypto Library. Depending upon the algorithm the library either overwrites these keys before returning control to the smartcard embedded software or provides a library call to through which the smartcard embedded software can clear these keys. In the case of a separate library call to clear keys the guidance instructs the smartcard embedded software when/how this call should be used.

Clearing of keys that are provided by the smartcard embedded software to the Crypto Library is the responsibility of the smartcard embedded software.

This SFR depends on the availability of the N7121 Crypto Library.

FCS_COP.1/AES_LIB

Cryptographic operation – AES – Crypto Library (optional)

FCS_COP.1.1/AES_LIB

The TSF shall perform *encryption, decryption and MAC generation* in accordance with a specified cryptographic algorithm *AES in ECB mode, CBC mode, CTR mode,*

CBC-MAC mode, and CMAC mode and cryptographic key sizes 128 bits, 192 bits, and 256 bits that meets the following:

- [\[FIPS 197\]](#) Section 5 (AES),
- [\[NIST SP 800-38A\]](#) Section 6.1, 6.2 and 6.5 (ECB, CBC and CTR mode),
- [\[ISO/IEC 9797-1\]](#), Algorithm 1 (CBC-MAC mode), and
- [\[NIST SP 800-38B\]](#) Section 6.2 (CMAC mode).

Application Note:

This SFR depends on the availability of the N7121 Crypto Library.

FCS_CKM.4/AES_LIB

Cryptographic Key Destruction – Crypto Library (optional)

FCS_CKM.4.1/AES_LIB

The TSF shall destroy cryptographic keys in accordance with a specified cryptographic key destruction method *flushing of key registers* that meets the following: *none*.

Application Note:

The N7121 Crypto Library provides the smartcard embedded software with library calls to perform various cryptographic algorithms that involve keys. Through the parameters of the library calls, the smartcard embedded software provides keys for the cryptographic algorithms. To perform its cryptographic algorithms, the library copies these keys, or a transformation thereof, to the working-buffer (supplied by the smartcard embedded software) and/or the memory/special function registers of the Crypto Library. Depending upon the algorithm the library either overwrites these keys before returning control to the smartcard embedded software or provides a library call to through which the smartcard embedded software can clear these keys. In the case of a separate library call to clear keys the guidance instructs the smartcard embedded software when/how this call should be used.

Clearing of keys that are provided by the smartcard embedded software to the Crypto Library is the responsibility of the smartcard embedded software.

This SFR depends on the availability of the N7121 Crypto Library.

6.1.4.2 Library Support for Random-Number Generation (optional)

The N7121 Crypto Library provides additional random-number generators as addressed by the following SFRs.

FCS_RNG.1/DRG.4

Random Number Generation – Hybrid Deterministic (optional)

FCS_RNG.1.1/DRG.4

The TSF shall provide a *hybrid deterministic* random number generator that implements:

(DRG.4.1) The internal state of the RNG shall use PTRNG of class PTG.2 as random source.

(DRG.4.2) The RNG provides forward secrecy.

(DRG.4.3) The RNG provides backward secrecy even if the current internal state is known.

(DRG.4.4) The RNG provides enhanced forward secrecy on demand.

(DRG.4.5) The internal state of the RNG is seeded by an PTRNG of class PTG.2.

FCS_RNG.1.2/DRG.4

The TSF shall provide *random numbers* that meet:

(DRG.4.6) The RNG generates output for which for AES-mode 2^{48} and for TDEA-mode 2^{35} strings of bit length 128 are mutually different with probability at least $1 - 2^{-24}$.

(DRG.4.7) Statistical test suites cannot practically distinguish the random numbers from output sequences of an ideal RNG. The random numbers must pass test procedure A.

Application Note:

The definition of this SFR is based on the already performed operations performed in [\[KS2011\]](#). Therefore, the operations indicated for FCS_RNG.1/DRG.4 are done here not with reference to [\[PP\]](#) where FCS_RNG.1 is defined but with respect to [\[KS2011\]](#).

Similar as in case of FCS_RNG.1/PTG.2, the additional standard statistical test suite in clause DRG.4.7 is left empty.

This SFR depends on the availability of the N7121 Crypto Library.

FCS_RNG.1/PTG.3

Random Number Generation (Hybrid-Physical) (optional)

FCS_RNG.1.1/PTG.3

The TSF shall provide a *hybrid physical* random number generator that implements:

(PTG.3.1) A total failure test detects a total failure of entropy source immediately when the RNG has started. When a total failure has been detected no random numbers will be output.

(PTG3.2) If a total failure of the entropy source occurs while the RNG is being operated, the RNG prevents the output of any internal random number that depends on

some raw random numbers that have been generated after the total failure of the entropy source

(PTG3.3) The online test shall detect non-tolerable statistical defects of the raw random number sequence (i) immediately when the RNG is started, and (ii) while the RNG is being operated. The TSF must not output any random numbers before the power-up online test and the seeding of the DRG.3 post-processing algorithm have been finished successfully or when a defect has been detected.

(PTG3.4) The online test procedure shall be effective to detect non-tolerable weaknesses of the random numbers soon.

(PTG3.5) The online test procedure checks the raw random number sequence. It is triggered continuously. The online test is suitable for detecting non-tolerable statistical defects of the statistical properties of the raw random numbers within an acceptable period of time.

(PTG3.6) The algorithmic post-processing algorithm belongs to Class DRG.3 with cryptographic state transition function and cryptographic output function, and the output data rate of the post-processing algorithm shall not exceed its input data rate.

FCS_RNG.1.2/PTG.3

The TSF shall provide numbers that meet:

(PTG3.7) Statistical test suites cannot practically distinguish the internal random numbers from output sequences of an ideal RNG. The internal random numbers must pass test procedure A.

(PTG3.8) The internal random numbers shall use PTRNG of class PTG.2 as random source for the post-processing.

Application Note:

The definition of this SFR is based on the already performed operations performed in [\[KS2011\]](#). Therefore, the operations indicated for FCS_RNG.1/DRG.4 are done here not with reference to [\[PP\]](#) where FCS_RNG.1 is defined but with respect to [\[KS2011\]](#).

This SFR depends on the availability of the N7121 Crypto Library.

6.1.4.3 Library Support for RSA (optional)

FCS_COP.1/RSA

Cryptographic operation – RSA (optional)

FCS_COP.1.1/RSA

The TSF shall perform *encryption, decryption, signature generation and verification* in accordance with a specified cryptographic algorithm *RSAEP, RSADP*,

RSASP1, RSAVP1, EME-OAEP and EMSA-PSS and cryptographic key sizes 1976 bits to 4096 bits that meets the following: [PKCS #1] Sections 5.1.1, 5.1.2, 5.2.1, 5.2.2, 7.1.1, 7.1.2, 9.1.1 and 9.1.2.

Application Note:

The security functionality is resistant against side channel analysis and other attacks described in [\[JIL-A TT-SC\]](#). To fend off attackers with high attack potential an adequate key length must be used (references can be found in national and international documents and standards).

This SFR depends on the availability of the N7121 Crypto Library.

The TOE additionally supports key sizes from 512 bits and under 1976 bits. However, these key sizes are not in the scope of evaluation.

The EME-OAEP encoding algorithm shall be used together with RSAEP and RSADP algorithms only.

The EMSA-PSS encoding algorithm shall be used together with RSASP1 and RSAVP1 algorithms only.

**FCS_CKM.5/
RSA_PubkeyDerivation**

Cryptographic key derivation – RSA public key computation (optional)

FCS_CKM.5.1/RSA_PubkeyDerivation

The TSF shall derive cryptographic keys *RSA public key* from *RSA private key* in accordance with a specified cryptographic key derivation algorithm *Computation of RSA public exponent from RSA private key in CRT form* and cryptographic key sizes *1976 bits to 4096 bits* that meet the following: *none*.

Application Note:

The security functionality is resistant against side channel analysis and other attacks described in [\[JIL-A TT-SC\]](#). To fend off attackers with high attack potential an adequate key length must be used (references can be found in national and international documents and standards).

The TOE additionally supports key sizes from 512 bits and under 1976 bits. However, these key sizes are not in the scope of evaluation.

The computation will result in the derivation of a RSA public key from the private key (in CRT format). As this key is implied by the private key, this is not true key generation, and, to prevent duplication in this ST, this has not been included as a separate FCS_CKM.1 SFR.

This SFR depends on the availability of the N7121 Crypto Library.

FCS_CKM.1/RSA_KeyGen **Cryptographic Key Generation – RSA (optional)**

FCS_CKM.1.1/RSA_KeyGen The TSF shall generate cryptographic keys in accordance with a specified cryptographic key generation algorithm *Generation of RSA keys* and specified cryptographic key sizes *1976 bits to 4096 bits (non FIPS compliance) and 2048 bits to 3072 bits (FIPS compliance)* that meet the following: [\[BAnz AT 30.01.2015 B3\]](#) (non FIPS compliance) and [\[FIPS 186-4\] Section B.3.3](#) (FIPS compliance).

Application Note:

The security functionality is resistant against side channel analysis. The implementation is also resistant against other attacks described in [\[JIL-ATT-SC\]](#) in case generated keys are used within the cryptographic library. To fend off attackers with high attack potential an adequate key length must be used (references can be found in national and international documents and standards).

For the modulus n ($n = p \cdot q$) the prime numbers p and q generated by the key generator are congruent to 3 modulo 4.

The TOE additionally supports key sizes from 512 bits and under 1976 bits. However, these key sizes are not in the scope of evaluation.

This SFR depends on the availability of the N7121 Crypto Library.

FCS_CKM.4/RSA **Cryptographic Key Destruction – RSA (optional)**

FCS_CKM.4.1/RSA The TSF shall destroy cryptographic keys in accordance with a specified cryptographic key destruction method *overwrite* that meets the following: [\[ISO 11568-4\] Section 6.11](#).

Application Note:

The crypto library provides the smartcard embedded software with library calls to perform various cryptographic algorithms that involve keys. Through the parameters of the library calls, the smartcard embedded software provides keys for the cryptographic algorithms. To perform its cryptographic algorithms, the library copies these keys, or a transformation thereof, to the working-buffer (supplied by the smartcard embedded software) and/or the memory/special function registers of the Crypto Library. Depending upon the algorithm the library either overwrites these keys before returning control to the smartcard embedded software or provides a library call to through which the smartcard embedded software can clear these keys. In the case of a separate

library call to clear keys the guidance instructs the smartcard embedded software when/how this call should be used.

Clearing of keys that are provided by the smartcard embedded software to the Crypto Library is the responsibility of the smartcard embedded software.

This SFR depends on the availability of the N7121 Crypto Library.

6.1.4.4 Library Support for Elliptic Curve Cryptography (optional)

FCS_COP.1/ECDSA

Cryptographic operation – ECDSA (optional)

FCS_COP.1.1/ECDSA

The TSF shall perform *signature generation and verification* in accordance with a specified cryptographic algorithm *ECDSA / ECC over GF(p)* and cryptographic key sizes *224, 256, 320, 384, 512 and 521 bits* that meets the following: [\[ISO/IEC 14888-3\] Sections 6.6.4 and 6.6.5](#), [\[ANSI X9.62-2005\] Section 7](#), [\[RFC 5639\] Sections 3.3, 3.4, 3.5, 3.6 and 3.7](#), [\[ANSSI 2011\]](#), [\[FIPS 186-4\] Section 6.4](#) and [\[IEEE Std 1363\] Sections 7.2.7 and 7.2.8](#).

Application Note:

The security functionality is resistant against side channel analysis and other attacks described in [\[JIL-A TT-SC\]](#). To fend off attackers with high attack potential an adequate key length must be used (references can be found in national and international documents and standards).

Due to BSI regulations the certification covers the standard curves *ansix9p224r1, ansix9p256r1, ansix9p384r1 and ansix9p521r1* from [ANSI X9.62 \[ANSI X9.62-1999\]](#), *brainpoolP224r1, brainpoolP224t1, brainpoolP256r1, brainpoolP256t1, brainpoolP320r1, brainpoolP320t1, brainpoolP384r1, brainpoolP384t1, brainpoolP512r1 and brainpoolP512t1* from [RFC 5639 \[RFC 5639\]](#) and [ANSSI FRP256v1 \[ANSSI 2011\]](#) curves.

This SFR depends on the availability of the N7121 Crypto Library.

FCS_COP.1/ECC_DHKE

Cryptographic operation – Diffie-Hellmann Key Exchange (optional)

FCS_COP.1.1/ECC_DHKE

The TSF shall perform *Cryptographic Key Exchange* in accordance with a specified cryptographic algorithm *ECDH / ECC over GF(p)* and cryptographic key sizes *224, 256, 320, 384, 512 and 521 bits* that meets the following: [\[ISO/IEC 11770-3\] Section B.5](#), [\[ANSI X9.63\]](#)

Section 6, [\[RFC 5639\]](#) Sections 3.3, 3.4, 3.5, 3.6 and 3.7, [\[ANSSI 2011\]](#) and [\[IEEE Std 1363\]](#) Section 9.2.

Application Note:

The security functionality is resistant against side channel analysis and other attacks described in [\[JIL-A TT-SC\]](#). To fend off attackers with high attack potential an adequate key length must be used (references can be found in national and international documents and standards).

The security functionality does not provide the complete key exchange procedure, but only the point multiplication which is used for the multiplication of the private key with the communication partner's public key. Therefore this function can be used as part of a Diffie-Hellman key exchange. In case of ECC library 0.7.7 for the release package R4, this function can also be used for pure point multiplication.

For curves `ansix9p256r1`, `ansix9p384r1`, `brainpoolP256r1`, `brainpoolP256t1`, `brainpoolP384r1`, `brainpoolP384t1`, `brainpoolP512r1`, `brainpoolP512t1`, `ANSSI FRP256v`, this function can also be used as pure point multiplication.

User guidance can be consulted for further information.

Due to BSI regulations the certification covers the standard curves `ansix9p224r1`, `ansix9p256r1`, `ansix9p384r1` and `ansix9p521r1` from ANSI X9.62 [\[ANSI X9.62-1999\]](#), `brainpoolP224r1`, `brainpoolP224t1`, `brainpoolP256r1`, `brainpoolP256t1`, `brainpoolP320r1`, `brainpoolP320t1`, `brainpoolP384r1`, `brainpoolP384t1`, `brainpoolP512r1` and `brainpoolP512t1` from RFC 5639 [\[RFC 5639\]](#) and ANSSI FRP256v1 [\[ANSSI 2011\]](#) curves.

This SFR depends on the availability of the N7121 Crypto Library.

FCS_CKM.1/ECC_KeyGen

Cryptographic Key Generation – ECC (optional)

FCS_CKM.1.1/ECC_KeyGen

The TSF shall generate cryptographic keys in accordance with a specified cryptographic key generation algorithm *Elliptic Curve Over GF(p) Key Pair Generation* and specified cryptographic key sizes *224, 256, 320, 384, 512 and 521 bits* that meet the following: [\[ISO/IEC 14888-3\]](#) Section 6.6.3, [\[ANSI X9.62-2005\]](#) Section A.4.3 and [\[FIPS 186-4\]](#) Section B.4.2.

Application Note:

The security functionality is resistant against side channel analysis and other attacks described in [\[JIL-A TT-SC\]](#). To fend off attackers with high attack potential an adequate key length must be used (references can

be found in national and international documents and standards).

Due to BSI regulations the certification covers the standard curves ansix9p224r1, ansix9p256r1, ansix9p384r1 and ansix9p521r1 from ANSI X9.62 [ANSI X9.62-1999], brainpoolP224r1, brainpoolP224t1, brainpoolP256r1, brainpoolP256t1, brainpoolP320r1, brainpoolP320t1, brainpoolP384r1, brainpoolP384t1, brainpoolP512r1 and brainpoolP512t1 from RFC 5639 [RFC 5639] and ANSSI FRP256v1 [ANSSI 2011] curves.

This SFR depends on the availability of the N7121 Crypto Library.

FCS_CKM.4/ECC

Cryptographic Key Destruction – ECC (optional)

FCS_CKM.4.1/ECC

The TSF shall destroy cryptographic keys in accordance with a specified cryptographic key destruction method *o verwrite* that meets the following: [ISO 11568-4] Section 6.11.

Application Note:

The crypto library provides the smartcard embedded software with library calls to perform various cryptographic algorithms that involve keys. Through the parameters of the library calls, the smartcard embedded software provides keys for the cryptographic algorithms. To perform its cryptographic algorithms, the library copies these keys, or a transformation thereof, to the working-buffer (supplied by the smartcard embedded software) and/or the memory/special function registers of the Crypto Library. Depending upon the algorithm the library either overwrites these keys before returning control to the smartcard embedded software or provides a library call to through which the smartcard embedded software can clear these keys. In the case of a separate library call to clear keys the guidance instructs the smartcard embedded software when/how this call should be used.

Clearing of keys that are provided by the smartcard embedded software to the Crypto Library is the responsibility of the smartcard embedded software.

This SFR depends on the availability of the N7121 Crypto Library.

6.1.4.5 Library Support for Hashing (optional)

Package "Hashing" defined in [PP].

FCS_COP.1/SHA

Cryptographic operation – Hashing (optional)

FCS_COP.1.1/SHA

The TSF shall perform *hashing* in accordance with a specified cryptographic algorithm *SHA-1, SHA-224, SHA-256, SHA-384, and SHA-512* and cryptographic key sizes *none* that meets the following: [\[FIPS 180-4\]](#).

Application Note:

During the evaluation of the SHA functions, no statement was made about DPA, CPA, and other comparable attacks. If the user wants to use applications that enable aforementioned attacks, like HMAC, further countermeasures need to be implemented or the security must be analyzed during the composite certification.

6.1.5 Further Security Functional Requirements – PUF (optional)**FCS_COP.1/AES_PUF****Cryptographic operation – PUF based AES****FCS_COP.1.1/AES_PUF**

The TSF shall perform *decryption and encryption* in accordance with a specified cryptographic algorithm *AES in CBC mode* and cryptographic key sizes *128 bits* that meets the following: [\[FIPS 197\]](#), [\[NIST SP 800-38A\]](#).

FCS_COP.1/MAC_PUF**Cryptographic operation – PUF based MAC****FCS_COP.1.1/MAC_PUF**

The TSF shall perform *MAC generation and calculation of CBC-MAC values used for PUF authentication* in accordance with a specified cryptographic algorithm *AES in CBC-MAC mode* and cryptographic key sizes *128 bits* that meets the following: [\[FIPS 197\]](#) and [\[ISO/IEC 9797-1\]](#) (MAC algorithm 1).

FCS_CKM.1/PUF**Cryptographic Key Generation – PUF****FCS_CKM.1.1/PUF**

The TSF shall generate cryptographic keys in accordance with a specified cryptographic key generation algorithm *key derivation function based on PUF* and specified cryptographic key sizes *128 bits* that meet the following: *>PUF Key derivation function specification, NXP Semiconductors, BUID, 2014. [PUF]*.

FCS_CKM.4/PUF**Cryptographic Key Destruction – PUF****FCS_CKM.4.1/PUF**

The TSF shall destroy cryptographic keys **derived by key derivation function based on PUF** in accordance with a specified cryptographic key destruction method *flushing of key registers* that meets the following: *none*.

6.1.6 Further Security Functional Requirements – Self-tests

FPT_TST.1

TSF Testing

FPT_TST.1.1

The TSF shall run a suite of self tests *at the request of the authorised user* to demonstrate the correct operation of *the active shielding and the sensors*.

FPT_TST.1.2

The TSF shall provide authorised users with the capability to verify the integrity of *Special Function Registers holding static values loaded during start-up*.

FPT_TST.1.3

The TSF shall provide authorised users with the capability to verify the integrity of *stored TSF executable code*.

Application Note:

In conformance with [\[CC_Part2\]](#), the TSF testing only addresses parts of the TSF. Therefore, the operations performed are selections and assignments which is indicated as *underlined italic text*. This is in conformance with the notation defined in [Section 6](#).

This SFR is in place for all configurations of the TOE.

6.1.7 Further Security Functional Requirements – Management Functions

FMT_SMF.1

Specification of Management Functions

FMT_SMF.1.1

The TSF shall be capable of performing the following management functions:

- *change of TOE mode to lower privileged mode by calling one of the following instructions: User Call,*
- *change of TOE mode to higher privileged mode by calling one of the following instructions: System Call,*
- *change of TOE mode by invoking an interrupt, and*
- *change of TOE mode by finishing an interrupt.*

Application Note:

This SFR is in place for all configurations of the TOE.

6.1.8 Further Security Functional Requirements – Access Control Policy

FDP_ACC.1/ACP

Subset Access Control – Access Control Policy

FDP_ACC.1.1/ACP

The TSF shall enforce the *Access Control Policy on all code running on the TOE, all memories and all memory operations*.

FDP_ACF.1/ACP	Security Attribute Based Access Control – Access Control Policy
FDP_ACF.1.1/ACP	The TSF shall enforce the <i>Access Control Policy</i> to objects based on the following: <i>TOE mode, memory access location, operation to be performed, permission control information</i> .
FDP_ACF.1.2/ACP	The TSF shall enforce the following rules to determine if an operation among controlled subjects and controlled objects is allowed: <i>evaluate the corresponding permission control information before the access so that accesses to be denied can not be utilised by the subject attempting to perform the operation</i> .
FDP_ACF.1.3/ACP	The TSF shall explicitly authorize access of subjects to objects based on the following additional rules: <i>none</i> .
FDP_ACF.1.4/ACP	The TSF shall explicitly deny access of subjects to objects based on the following additional rules: <i>none</i> .
FMT_MSA.1/ACP	Management of Security Attributes – Access Control Policy
FMT_MSA.1.1/ACP	The TSF shall enforce the <i>Access Control Policy</i> to restrict the ability to <i>modify</i> the security attributes <i>permission control information to code executed in a TOE mode which has write access to the memory location where the permission control information is stored</i> .
Application Note:	This SFR is in place for all configurations of the TOE.
FMT_MSA.3/ACP	Static Attribute Initialization – Access Control Policy
FMT_MSA.3.1/ACP	The TSF shall enforce the <i>Access Control Policy</i> to provide <i>restrictive</i> default values for security attributes that are used to enforce the SFP.
FMT_MSA.3.2/ACP	The TSF shall allow <i>no subject</i> to specify alternative initial values to override the default values when an object or information is created.

6.2 Security assurance requirements

[Table 18](#) lists all security assurance requirements that are valid for this Security Target. These security assurance requirements are defined in [\[PP\]](#) and/or in [\[CC_Part3\]](#) for EAL6, except for requirements ASE_TSS.2 and ALC_FLR.1, which are augmentations of this Security Target to EAL6, see [Section 2.2](#). ASE_TSS.2 is an augmentation in this Security Target to give architectural information on the security functionality of the TOE.

ALC_FLR.1 is an augmentation in this Security Target to cover policies and procedures of the developer applied to track and correct flaws and support surveillance of the TOE.

In compliance with Application Note 22 in [PP] the third column in Table 18 shows, which Security Assurance Requirements (SARs) are added to this Security Target compared to [PP]. In this context, entry "EAL6 / PP" means, that the requirement is defined in both, [CC_Part3] for EAL6 and [PP], entry "EAL6" means, that the requirement is defined in [CC_Part3] for EAL6 but not in [PP], and entry "ST" means, that the requirement is defined neither in [CC_Part3] for EAL6 nor in [PP], but in this Security Target.

All refinements of the security assurance requirements in the [PP], which must be adapted for EAL6, are described in this section.

Table 18. SARs for this ST

SAR	Title	Required by
ADV_ARC.1	Security architecture description	EAL6 / PP
ADV_FSP.5	Complete semi-formal functional specification with additional error information	EAL6
ADV_IMP.2	Complete mapping of the implementation representation of the TSF	EAL6
ADV_INT.3	Minimally complex internals	EAL6
ADV_TDS.5	Complete semiformal modular design	EAL6
ADV_SPM.1	Formal TOE security policy model	EAL6
AGD_OPE.1	Operational user guidance	EAL6 / PP
AGD_PRE.1	Preparative procedures	EAL6 / PP
ALC_CMC.5	Advanced support	EAL6
ALC_CMS.5	Development tools CM coverage	EAL6
ALC_DEL.1	Delivery procedures	EAL6 / PP
ALC_DVS.2	Sufficiency of security measures	EAL6 / PP
ALC_FLR.1	Basic flaw remediation	ST
ALC_LCD.1	Developer defined life-cycle model	EAL6 / PP
ALC_TAT.3	Compliance with implementation standards – all parts	EAL6
ASE_CCL.1	Conformance claims	EAL6 / PP
ASE_ECD.1	Extended components definition	EAL6 / PP
ASE_INT.1	ST introduction	EAL6 / PP
ASE_OBJ.2	Security objectives	EAL6 / PP
ASE_REQ.2	Derived security requirements	EAL6 / PP
ASE_SPD.1	Security problem definition	EAL6 / PP
ASE_TSS.2	TOE summary specification with architectural design summary	ST
ATE_COV.3	Rigorous analysis of coverage	EAL6
ATE_DPT.3	Testing: modular design	EAL6
ATE_FUN.2	Ordered functional testing	EAL6
ATE_IND.2	Independent testing – sample	EAL6 / PP

Table 18. SARs for this ST...continued

SAR	Title	Required by
AVA_VAN.5	Advanced methodical vulnerability analysis	EAL6 / PP

In the set of assurance components chosen for EAL6, the assignment appears only in ADV_SPM.1. The assignment for ADV_SPM.1 is defined below.

- ADV_SPM.1** Formal TOE security policy model
- ADV_SPM.1.1D** The developer shall provide a formal security policy model for the following SFRs
 - Limited Capability and Availability Policy: FMT_LIM.1 and FMT_LIM.2
 - Access Control Policy: FDP_ACC.1/ACP, FDP_ACF.1/ACP, FMT_MSA.1/ACP, FMT_MSA.3/ACP and FMT_SMF.1
 - Loader SFP: FDP_ACC.1/Loader, FDP_ACF.1/Loader, FDP_UCT.1/Loader, FDP_UIT.1/Loader, FMT_LIM.1/Loader, FMT_LIM.2/Loader and FTP_ITC.1/Loader.
 - Other partly modelled SFRs: FAU_SAS.1 and FPT_FLS.1, and FPT_TST.1.
- ADV_SPM.1.2D** For each policy covered by the formal security policy model, the model shall identify the relevant portions of the statement of SFRs that make up that policy.
- ADV_SPM.1.3D** The developer shall provide a formal proof of correspondence between the model and any formal functional specification.
- ADV_SPM.1.4D** The developer shall provide a demonstration of correspondence between the model and the functional specification.

6.3 Security requirements rationale

6.3.1 Rationale for the Security Functional Requirements

Section 6.3.1 in [PP] provides a rationale for the mapping between security functional requirements and security objectives defined in [PP]. The mapping is reproduced in the following table. Note that, only TOE objectives are listed since no SFRs are mapped to objectives related to operational resp. development environment.

Table 19. Mapping of the Security Objectives for the TOE to the Security Functional Requirements for the TOE

Objective	SFR	Rationale
Objectives of the Protection Profile [PP]		
O.Leak-Inherent	FDP_ITT.1	See [PP].

Table 19. Mapping of the Security Objectives for the TOE to the Security Functional Requirements for the TOE...continued

Objective	SFR	Rationale
	FDP_IFC.1	See [PP].
	FPT_ITT.1	See [PP].
O.Phys-Probing	FDP_SDC.1	See [PP].
	FPT_PHP.3	See [PP].
O.Malfunction	FPT_FLS.1	See [PP].
	FRU_FLT.2	See [PP].
O.Phys-Manipulation	FDP_SDI.2	See [PP].
	FPT_PHP.3	See [PP].
O.Leak-Forced	FDP_ITT.1	See [PP].
	FDP_IFC.1	See [PP].
	FPT_FLS.1	See [PP].
	FPT_ITT.1	See [PP].
	FPT_PHP.3	See [PP].
	FRU_FLT.2	See [PP].
O.Abuse-Func	FDP_ITT.1	See [PP].
	FDP_IFC.1	See [PP].
	FMT_LIM.1	See [PP].
	FMT_LIM.2	See [PP].
	FPT_FLS.1	See [PP].
	FPT_ITT.1	See [PP].
	FPT_PHP.3	See [PP].
	FRU_FLT.2	See [PP].
O.Identification	FAU_SAS.1	See [PP].
O.RND	FCS_RNG.1/PTG.2	See [PP].
	FDP_ITT.1	See [PP].
	FDP_IFC.1	See [PP].
	FPT_FLS.1	See [PP].
	FPT_ITT.1	See [PP].
	FPT_PHP.3	See [PP].
	FRU_FLT.2	See [PP].
	FCS_RNG.1/PTG.3	The PTG.3 random number generator provided by the crypto library (if available) corresponds to a hybrid-physical random number generator. As an alternative to the physical true random number generator, this RNG corresponds to the objective O.RND.

Table 19. Mapping of the Security Objectives for the TOE to the Security Functional Requirements for the TOE...continued

Objective	SFR	Rationale
	FCS_RNG.1/DRG.4	The DRG.4 random number generator provided by the crypto library (if available) corresponds to a hybrid-deterministic random number generator. As an alternative to the physical true random number generator, this RNG corresponds to the objective O.RND.
O.Cap_Avail_Loader	FMT_LIM.1/Loader	See [PP].
	FMT_LIM.2/Loader	See [PP].
O.Ctrl_Auth_Loader	FDP_ACC.1/Loader	See [PP].
	FDP_ACF.1/Loader	See [PP].
	FDP_UCT.1/Loader	See [PP].
	DP_UIT.1/Loader	See [PP].
	FTP_ITC.1/Loader	See [PP].
O.TDES	FCS_COP.1/TDES	See [PP].
	FCS_CKM.4/TDES	See [PP].
	FCS_COP.1/TDES_LIB	See [PP].
	FCS_CKM.4/TDES_LIB	See [PP].
O.AES	FCS_COP.1/AES	See [PP].
	FCS_CKM.4/AES	See [PP].
	FCS_COP.1/AES_LIB	See [PP].
	FCS_CKM.4/AES_LIB	See [PP].
O.SHA	FCS_COP.1/SHA	See [PP].
Additional objectives defined in this ST		
O.NVM-Integrity	FDP_SDI.2	The objective requires integrity protection and correction of failures of data stored in the Flash memory.The SFR describes this functionality for all memories.
O.Mem-Access O.Secure-User-Mode-Box (optional)	FDP_ACC.1/ACP	The objective requires access control to memories and special function registers. This is covered by the SFRs which define the access control policy. The SFRs also cover the additional and optional functionality of the NXP Secure User Mode Box defined by O.Secure-User-Mode-Box. The SFR FMT_SMF.1 requires functionality to change the TOE mode in a controlled way using User and System Calls or via interrupts triggered by hardware peripherals as described in O.Mem-Access. The Access Control Policy is based on these TOE modes.
	FMT_MSA.1/ACP	
	FMT_MSA.3/ACP	
	FDP_ACF.1/ACP	
	FMT_SMF.1	

Table 19. Mapping of the Security Objectives for the TOE to the Security Functional Requirements for the TOE...continued

Objective	SFR	Rationale
O.Self-Test	FPT_TST.1	The objective described self-test functionality to detect physical manipulation. The SFR FPT_TST.1 addresses the objective as it requires tests of the active shielding and sensors, integrity check of special function registers on start-up, and integrity check of stored TSF executable code.
O.PUF	FCS_COP.1/AES_PUF	The objective describes sealing and unsealing of user data using the device-specific PUF. This comprises encryption/decryption (FCS_COP.1/AES_PUF) and MAC calculation (FCS_COP.1/MAC_PUF). The SFRs FCS_CKM.1/PUF and FCS_CKM.4/PUF describe the generation and destruction of the device specific PUF key during start-up and shut down, respectively.
	FCS_COP.1/MAC_PUF	
	FCS_CKM.1/PUF	
	FCS_CKM.4/PUF	
O.RSA	FCS_COP.1/RSA FCS_CKM.5/RSA_PubkeyDerivation FCS_CKM.1/RSA_KeyGen FCS_CKM.4/RSA	The SFRs directly implement the functionality required by the objective.
O.ECC	FCS_COP.1/ECDSA FCS_COP.1/ECC_DHKE FCS_CKM.1/ECC_KeyGen FCS_CKM.4/ECC	The SFRs directly implement the functionality required by the objective.

6.3.2 Dependencies of the Security Functional Requirements

The dependencies listed in [PP] are independent of the additional dependencies listed in the table below.

The dependencies of the PP are fulfilled within the PP and at least one dependency is considered to be satisfied.

The following discussion demonstrates how the dependencies defined by Part 2 of the Common Criteria [CC_Part2] for the requirements specified in Section 6.1 and Section 6.2 are satisfied.

The dependencies defined in the Common Criteria are listed in the table below.

Table 20. Dependencies of the Security Functional Requirements for the TOE

SFR	Dependencies	Fulfilled by
SFRs of the Protection Profile		
FRU_FLT.2	FPT_FLS.1	See [PP].
FPT_FLS.1	--	See [CC_Part2].
FMT_LIM.1	FMT_LIM.2	See [PP].

Table 20. Dependencies of the Security Functional Requirements for the TOE...continued

SFR	Dependencies	Fulfilled by
FMT_LIM.2	FMT_LIM.1	See [PP] .
FAU_SAS.1	--	See [PP] .
FDP_SDC.1	--	See [PP] .
FDP_SDI.2	--	See [CC_Part2] .
FPT_PHP.3	--	See [CC_Part2] .
FDP_ITT.1	FDP_ACC.1 or FDP_IFC.1	See [PP] .
FPT_ITT.1	--	See [CC_Part2] .
FDP_IFC.1	FDP_IFF.1	See [PP] .
FCS_RNG.1/PTG.2	--	See [PP] .
SFRs of the Loader Packages of the Protection Profile		
FMT_LIM.1/Loader	FMT_LIM.2	See [PP] .
FMT_LIM.2/Loader	FMT_LIM.1	See [PP] .
FTP_ITC.1/Loader	--	See [CC_Part2] .
FDP_UCT.1/Loader	FTP_ITC.1 or FTP_TRP.1 FDP_ACC.1 or FDP_IFC.1	See [PP] .
FDP_UIT.1/Loader	FDP_ACC.1 or FDP_IFC.1 FTP_ITC.1 or FTP_TRP.1	See [PP] .
FDP_ACC.1/Loader	FDP_ACF.1	See [PP] .
FDP_ACF.1/Loader	FDP_ACC.1 FMT_MSA.3	See [PP] .
SFRs of the package "TDES" defined in the Protection Profile (partly optional)		
FCS_COP.1/TDES	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	See [PP] . Key import or key generation has to be fulfilled by the Security IC Embedded Software.
FCS_COP.1/TDES_LIB (optional)	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Partly fulfilled by FCS_CKM.4/TDES_LIB. Key import or key generation has to be fulfilled by the Security IC Embedded Software.
FCS_CKM.4/TDES	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1	See [PP] . Key import or key generation has to be fulfilled by the Security IC Embedded Software.
FCS_CKM.4/TDES_LIB (optional)	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1	See FCS_CKM.4/TDES. Key import or key generation has to be fulfilled by the Security IC Embedded Software.
SFRs of the package "AES" defined in the Protection Profile (partly optional)		
FCS_COP.1/AES	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	See [PP] . Key import or key generation has to be fulfilled by the Security IC Embedded Software.

Table 20. Dependencies of the Security Functional Requirements for the TOE...continued

SFR	Dependencies	Fulfilled by
FCS_COP.1/AES_LIB (optional)	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Partly fulfilled by FCS_CKM.4/AES_LIB. Key import or key generation has to be fulfilled by the Security IC Embedded Software.
FCS_CKM.4/AES	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1	See [PP] . Key import or key generation has to be fulfilled by the Security IC Embedded Software.
FCS_CKM.4/AES_LIB (optional)	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1	See FCS_CKM.4/AES. Key import or key generation has to be fulfilled by the Security IC Embedded Software.
SFRs from the optional package "Hashing" defined in the Protection Profile		
FCS_COP.1/SHA	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	See [PP] . As no key is used, there is no need for key import as required by dependency to FDP_ITC.1 or FDP_ITC.2 or key generation as required by FCS_CKM.1 or key destruction as required by the dependency to FCS_CKM.4. Therefore, there is no need to fulfill the dependencies.
Further SFRs defined in this ST		
FCS_COP.1/AES_PUF	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Fulfilled by FCS_CKM.1/PUF and FCS_CKM.4/PUF.
FCS_COP.1/MAC_PUF	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Fulfilled by FCS_CKM.1/PUF and FCS_CKM.4/PUF.
FCS_CKM.1/PUF	FCS_CKM.2 or FCS_COP.1 FCS_CKM.4	Fulfilled by FCS_COP.1/AES_PUF, FCS_COP.1/MAC_PUF and FCS_CKM.4/PUF.
FCS_CKM.4/PUF	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1	Fulfilled by FCS_CKM.1/PUF.
FPT_TST.1	--	See [CC_Part2] .
FMT_SMF.1	--	See [CC_Part2] .
FDP_ACC.1/ACP	FDP_ACF.1	Fulfilled by FDP_ACF.1/ACP.
FDP_ACF.1/ACP	FDP_ACC.1 FMT_MSA.3	Fulfilled by FDP_ACC.1/ACP and FMT_MSA.3/ACP.
FMT_MSA.1/ACP	FDP_ACC.1 or FDP_IFC.1, FMT_SMR.1 FMT_SMF.1	Partly fulfilled by FDP_ACC.1/ACP and FMT_SMF.1. FMT_SMR.1: See discussion below.
FMT_MSA.3/ACP	FMT_MSA.1 FMT_SMR.1	Partly fulfilled by FMT_MSA.1/ACP. FMT_SMR.1: See discussion below.
FCS_RNG.1/DRG.4	--	See [PP] .

Table 20. Dependencies of the Security Functional Requirements for the TOE...continued

SFR	Dependencies	Fulfilled by
FCS_RNG.1/PTG.3	--	See [PP].
FCS_COP.1/RSA	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Fulfilled by FCS_CKM.1/RSA_KeyGen and FCS_CKM.4/RSA.
FCS_CKM.5/RSA_PubkeyDerivation	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Fulfilled by FCS_CKM.1/RSA_KeyGen and FCS_CKM.4/RSA.
FCS_COP.1/ECDSA	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Fulfilled by FCS_CKM.1/ECC_KeyGen and FCS_CKM.4/ECC.
FCS_COP.1/ECC_DHKE	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1 FCS_CKM.4	Fulfilled by FCS_CKM.1/ECDSA and FCS_CKM.4/ECC.
FCS_CKM.1/RSA_KeyGen	FCS_CKM.2 or FCS_COP.1 FCS_CKM.4	Fulfilled by FCS_COP.1/RSA and FCS_CKM.4/RSA.
FCS_CKM.1/ECC_KeyGen	FCS_CKM.2 or FCS_COP.1 FCS_CKM.4	Fulfilled by FCS_COP.1/ECDSA, FCS_COP.1/ECC_DHKE and FCS_CKM.4/ECC.
FCS_CKM.4/RSA	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1	Fulfilled by FCS_CKM.1/RSA_KeyGen.
FCS_CKM.4/ECC	FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1	Fulfilled by FCS_CKM.1/ECC_KeyGen.

Note: Please note that the partly fulfilled dependencies of the SFRs mapped to O.AES and O.TDES are given in case the crypto library is available or not. Even without the crypto library, the TSF provides functionality to destruct key as specified by FCS_CKM.4/ AES and FCS_CKM.4/TDES, respectively. In any case, the Security IC Embedded Software has to implement key generation required by the missing dependency to FCS_CKM.1 of the hardware functionality and the functionality provided by the crypto library.

Note: The dependency to FMT_SMR.1 introduced by the components FMT_MSA.1/ACP and FMT_MSA.3/ACP is not applicable within the context of the SFRs. No additional definition of roles is required, as all necessary roles are already realized via the modes of the MMU. No actions by the Security IC Embedded Software Developer is required to implement those roles. In conclusion, these dependencies are not applicable.

Note: The dependency to FMT_MSA.3 introduced by the component FDP_ACF.1/ Loader is not applicable within the context of the SFRs. It is because all the security attributes used to enforce Loader SP and objects are already fixed and defined by NXP as described in Table 17.

6.3.3 Refinements of the TOE Security Assurance Requirements

In compliance to Application Note 23 of [PP] this Security Target has to conform to all refinements of the security assurance requirements in [PP]. These refinements are defined for the Security Assurance Requirements of EAL4. Thus, some of these refinements must be adapted to Security Assurance Requirements of higher levels according to EAL6 as claimed in this Security Target. All other Security Assurance

Requirements defined in this Security Target and in particular the augmentations to EAL6 supplement and extend the Security Assurance Requirements in the [PP] and can be added without contradictions.

Table 21 lists all Security Assurance Requirements that are refined in the [PP] based on their definitions in [CC_Part3] and their effect on this Security Target.

Table 21. SARs refined in PP and their effect on this ST

Refined SAR in PP	Affected SAR in this ST	Rationale
ADV_ARC.1	ADV_ARC.1	SAR same as in [PP], refinement valid without change
ADV_FSP.4	ADV_FSP.5	<p>The refinement in Section 6.2.1.6 of [PP] regarding ADV_FSP.4 addresses the complete representation of the TSF, the purpose and method of use of all TSFIs, and the accuracy and completeness of the SFR instantiations. The refinement is not a change in the wording of the action elements, but a more detailed definition of the items above. Compared to ADV_FSP.4 component ADV_FSP.5 requires a Functional Specification in a "semi-formal style" (ADV_FSP.5.2C). In addition, component ADV_FSP.5 extends the scope of the error messages to be described from those resulting from an invocation of a TSFI (ADV_FSP.5.6C) to also those not resulting from an invocation of a TSFI (ADV_FSP.5.7C). For the latter a rationale shall be provided (ADV_FSP.5.8C).</p> <p>Since the higher level ADV_FSP.5 only affects the style of description and the scope of and rationale for error messages, the refinement in the [PP] regarding ADV_FSP.4 can be applied without changes and is valid for ADV_FSP.5.</p>
ADV_IMP.1	ADV_IMP.2	<p>The refinement in Section 6.2.1.7 of [PP] regarding ADV_IMP.1 states that it must be checked that the provided implementation representation is complete and sufficient to ensure that analysis activities are not curtailed due to lack of information.</p> <p>This Security Target targets assurance level EAL6 augmented, which requires access to all source code of the TOE so that the above refinement is implicitly fulfilled.</p>
AGD_OPE.1	AGD_OPE.1	SAR same as in [PP], refinement valid without change.
AGD_PRE.1	AGD_PRE.1	SAR same as in [PP], refinement valid without change.
ALC_CMC.4	ALC_CMC.5	<p>The refinement in Section 6.2.1.4 of [PP] regarding ALC_CMC.4 is a clarification of the "TOE" and the term "configuration items".</p> <p>Since the higher level ALC_CMC.5 requires a higher assurance regarding the defined TOE and the configuration items, the refinement in [PP] regarding ADV_CMC.4 can be applied without changes and is valid for ADV_CMC.5.</p>
ALC_CMS.4	ALC_CMS.5	<p>The refinement in Section 6.2.1.3 of [PP] regarding ALC_CMS.4 is a clarification of the configuration item "TOE implementation representation".</p> <p>Compared to ALC_CMS.4 component ALC_CMS.5 only adds the requirement for a new configuration item to be included in the configuration list (ALC_CMS.51C) so that the refinement in the [PP] regarding ADV_CMS.4 can be applied without changes and is valid for ADV_CMS.5.</p>

Table 21. SARs refined in PP and their effect on this ST...continued

Refined SAR in PP	Affected SAR in this ST	Rationale
ALC_DEL.1	ALC_DEL.1	Same as in [PP], refinement valid without change.
ALC_DVS.2	ALC_DVS.2	Same as in [PP], refinement valid without change.
ATE_COV.2	ATE_COV.3	<p>The refinement in Section 6.2.1.8 of [PP] regarding ATE_COV.2 defines that test coverage must include different operating conditions and "ageing" and that existence and effectiveness of countermeasures against physical attacks cannot be tested but must be given by evidence.</p> <p>The refinement regarding test coverage is not a change in the wording of the action elements, but a more detailed definition of the items to be applied, so that it can be applied without changes and is valid for ATE_COV.3. The refinement regarding existence and effectiveness of countermeasures against physical attacks is implicitly fulfilled since this Security Target targets assurance level EAL6 augmented, which requires access to all source code and layout data</p>
AVA_VAN.5	AVA_VAN.5	<p>Same as in [PP], refinement valid without change.</p> <p>Note: As required by Application Note 29 of the [PP], [JIL-ATT-SC] was utilized in its current version for the vulnerability analysis. The version is further more indicated in the reference list.</p>

6.3.4 Rationale for the Security Assurance Requirements

The selection of assurance components is based on the underlying [PP]. The Security Target uses the same augmentations as the PP (and the addition of augmentations ASE_TSS.2 and ALC_FLR.1), but chooses a higher assurance level. The level EAL6 is chosen in order to meet assurance expectations of digital signature applications and electronic payment systems. Additionally, the requirement of the PP to choose at least EAL4 is fulfilled.

The rationale for the PP augmentations is the same as in the PP. The assurance level EAL6 is an elaborated pre-defined level of the [CC Part3]. The assurance components in an EAL level are chosen in a way that they build a mutually supportive and complete set of components. The requirements chosen for augmentation do not add any dependencies, which are not already fulfilled for the corresponding requirements contained in EAL6.

Therefore, these components add additional assurance to EAL6, but the mutual support of the requirements is still guaranteed.

As stated in the Section 6.3.3 of [PP], the TOE is intended to defend against sophisticated attacks. Therefore specifically AVA_VAN.5 was chosen by the PP in order to assure that even attackers with high attack potential cannot successfully attack the TOE.

In addition to the SARs introduced by EAL6, the following augmentations have been added:

- ASE_TSS.2 was chosen to include architectural information on the security functionality of the TOE in the ST.

- ALC_FLR.1 was chosen to prove that NXP tracks and corrects security flaws.

6.3.5 Security requirements are internally consistent

The discussion of security functional requirements and assurance components in the preceding sections has shown that mutual support and consistency are given for both groups of requirements. The arguments given for the fact that the assurance components are adequate for the functionality of the TOE also show that the security functional and assurance requirements support each other and that there are no inconsistencies between these groups.

The security functional requirements required to meet the security objectives O.Leak-Inherent, O.Phys-Probing, O.Malfunction, O.Phys-Manipulation and O.Leak-Forced also protect the cryptographic algorithms and the memory access/separation control function as well as the access control to Special Function Registers implemented according to the security functional requirements FDP_MSA.1/ACP, FDP_MSA.3/ACP and FDP_ACC.1/ACP, with reference to the Access Control Policy defined in FDP_ACF.1/ACP. Therefore, these Security Objectives support the secure implementation and operation of FDP_MSA.1/ACP, FDP_MSA.3/ACP and of FDP_ACC.1/ACP with FDP_ACF.1/ACP as well as the dependent security functional requirements.

A Security IC hardware platform requires Security IC Embedded Software to build a secure product. Thereby the Security IC Embedded Software must support the security functionality of the hardware and implement a sufficient management of the security services implemented in the hardware. The realization of the Security Functional Requirements within the TOE provides a good balance between flexible configuration and restrictions to ensure a secure behavior of the TOE.

7 TOE summary specification

7.1 Portions of the TOE Security Functionality

The TOE Security Functionality (TSF) directly corresponds to the TOE security functional requirements defined in Section 6.1 which are active and applicable to phases 4 to 7 of the Security IC product life-cycle defined in Section 1.2.3 of the [PP].

Note: Please note that parts of the security functionality are configured at the end of phase 3 and all security functionality is active after phase 3 or phase 4 depending on the delivery form.

Table 22. Portions of the TSF

TSF portion	Title	Description
TSF.Service	Service functionality beside cryptographic operations	This portion of the TSF comprises random number generation, reconfiguration of the TOE features, self-test functionality, as well as a secure channel for using the Flash Loader. It further provides mechanisms to store initialization, pre-personalization, and/or other data on the TOE.
TSF.Protection	General security measures to protect the TSF	This portion of the TSF comprises physical and logical protection to avoid information leakage and detect fault injection. It defines resets in case an error or attack was detected and guarantees that memories used by the optional available cryptographic libraries are cleared before other applications can access these memories.
TSF.Control	Operating conditions, memory and hardware access control	This portion of the TSF controls the operating conditions and manages the access rights to memories and peripherals for the different TOE modes.
TSF.Crypto	Crypto Service	This portion of the TSF provides cryptographic functionality such as TDES and AES in different modes depending on the availability of the N7121 Crypto Library. Furthermore, based on the availability of the N7121 Crypto Library, TSF.Crypto also covers asymmetric cryptography (RSA and ECC over GF(p)) and hashing.

7.2 TOE summary specification rationale

7.2.1 Mapping of Security Functional Requirements and TOE security functionality

The following table provides a mapping of portions of the TSF to SFRs. The table also provides information which aspect of the TSF covered by each SFR.

Table 23. Mapping of SFRs to portions of the TSF

SFR	TSF.Service	TSF.Protection	TSF.Control	TSF.Crypto	Description
SFRs of the Protection Profile					
FRU_FLT.2			X		Controls the operating conditions.
FPT_FLS.1		O	X		If the operating conditions are out of bounds, the TSF triggers a reset which restores a Secure State.
FMT_LIM.1			X		Blocking of test features after TOE delivery.
FMT_LIM.2			X		Blocking of test features after TOE delivery.
FAU_SAS.1	X				Store initialization data, pre-personalization data, and/or other data on the TOE
FDP_SDC.1		X			Memory data confidentiality.
FDP_SDI.2		X			Detects and counters integrity errors of data stored in memories.
FPT_PHP.3		X			Physical manipulation.
FDP_ITT.1		X			Information flow control to avoid information leakage.
FPT_ITT.1		X			Information flow control to avoid information leakage.
FDP_IFC.1		X			Information flow control to avoid information leakage.
FCS_RNG.1/PTG.2	X				Random number generation.
SFRs of the Loader Packages					
Loader Package 1 defined in the [PP]					
FMT_LIM.1/Loader			X		No disclosure of user data.
FMT_LIM.2/Loader			X		Block loader.
Loader Package 2 defined in the [PP] (optional)					
FTP_ITC.1/Loader	X	O			Trusted channel for using the loader.
FDP_UCT.1/Loader		X			Protect from unauthorized disclosure.
FDP_UIT.1/Loader		X			Protect from modification, deletion, insertion.
FDP_ACC.1/Loader			X		Defines on which Subjects and Objects the Loader SFP is applied.
FDP_ACF.1/Loader			X		Defines the Loader SFP.
SFRs of the Hardware Support for TDES and AES					
Package TDES defined in [PP]					
FCS_COP.1/TDES		O		X	TDES hardware support.
FCS_CKM.4/TDES		O		X	Destruction of cryptographic keys used by the TDES coprocessor.
Package "AES" defined in [PP]					
FCS_COP.1/AES		O		X	AES hardware support.
FCS_CKM.4/AES		O		X	Destruction of cryptographic keys used by the AES coprocessor.
SFRs related to the crypto library (optional)					

Table 23. Mapping of SFRs to portions of the TSF...continued

SFR	TSF.Service	TSF.Protection	TSF.Control	TSF.Crypto	Description
Package Symmetric Ciphers (optional)					
FCS_COP.1/TDES_LIB		O		X	TDES library support.
FCS_COP.1/AES_LIB		O		X	AES library support.
FCS_CKM.4/TDES_LIB		O		X	Destruction of cryptographic keys used by the crypto library.
FCS_CKM.4/AES_LIB		O		X	
Package Random Number Generation (optional)					
FCS_RNG.1/DRG.4	X				Random number generation.
FCS_RNG.1/PTG.3	X				
Package RSA Encryption/Decryption and RSA Key Generation (optional)					
FCS_COP.1/RSA		O		X	RSA encryption, decryption, signature generation and verification.
FCS_CKM.5/RSA_PubkeyDerivation		O		X	RSA public key derivation.
FCS_CKM.1/RSA_KeyGen				X	RSA key generation.
FCS_CKM.4/RSA		O		X	RSA key destruction.
Package ECC over GF(p) (optional)					
FCS_COP.1/ECDSA		O		X	ECDSA signature generation and verification.
FCS_COP.1/ECC_DHKE		O		X	Diffie-Hellmann Key Exchange via ECC over GF(p).
FCS_CKM.1/ECC_KeyGen				X	ECC key generation.
FCS_CKM.4/ECC		O		X	ECDSA key destruction.
SHA functionality defined in [PP] (optional)					
FCS_COP.1/SHA		O		X	Hashing with SHA-1, SHA-224, SHA-256, SHA-384, and SHA-512.
SFRs related to PUF					
FCS_COP.1/AES_PUF		O		X	AES-128 in CBC mode with PUF key.
FCS_COP.1/MAC_PUF		O		X	AES-128 in CBC-MAC mode with PUF key.
FCS_CKM.1/PUF				X	Key generation based on PUF.
FCS_CKM.4/PUF		O		X	Destruction of keys generated by PUF.
SFRs related to self-tests					
FPT_TST.1	X	O			Self-tests of TSF.
SFRs related to management functions					
FMT_SMF.1			X		Change of TOE modes via User Calls, System Calls and interrupts triggered by hardware peripherals.

Table 23. Mapping of SFRs to portions of the TSF...continued

SFR	TSF.Service	TSF.Protection	TSF.Control	TSF.Crypto	Description
SFRs related to the Access Control Policy					
FDP_ACC.1/ACP			X		Application of the ACP on Objects and Subjects.
FDP_ACF.1/ACP			X		Definition of the ACP.
FMT_MSA.1/ACP			X		Restrictive modification of ACP attributes of the defined objects by the defined subjects.
FMT_MSA.3/ACP			X		Restrictive default values for the ACP.

In the table above, 'X' indicates a direct mapping between SFR and portion of the TSF while 'O' indicates an indirect mapping

7.2.2 Security Architectural Information

Since this ST claims the assurance requirement ASE_TSS.2, security architectural information on a very high level is supposed to be included in the TSS to inform potential customers on how the TOE protects itself against interference, logical tampering and bypassing. In the security architecture context, this covers the aspects self-protection and non-bypassability. The aspects self-protection and non-bypassability are for a large part covered by TSF.Protection and TSF.Control. TSF.Protection covers the physical and logical protection of the TOE and protects the TOE against tampering and bypassing of security features and security services. It contributes by covering the aspects failure with preservation of a secure state and limited fault tolerance. This protects the TOE against interference of security feature and security services. TSF.Control limits the capability and availability of the Test Features and protects the TOE against bypassing of security features. In addition to the protection against interference, tampering and bypassing provided by TSF.Protection and TSF.Control, TSF.Service also contributes to the self-protection of the TOE and non-bypassing of security functionality.

8 References

[AIS20]	<i>Anwendungshinweise und Interpretationen zum Schema (AIS), Funktionalitätsklassen und Evaluationsmethodologie für deterministische Zufallszahlengeneratoren</i> , Version 3, 2013-05-15, Bundesamt für Sicherheit in der Informationstechnik.
[AIS26]	<i>Anwendungshinweise und Interpretationen zum Schema (AIS), AIS 26, Evaluationsmethodologie für in Hardware integrierte Schaltungen</i> , Version 9, 2013-03-21, Bundesamt für Sicherheit in der Informationstechnik.
[AIS31]	<i>Anwendungshinweise und Interpretationen zum Schema (AIS), AIS 31, Funktionalitätsklassen und Evaluationsmethodologie für physikalische Zufallszahlengeneratoren</i> , Version 3, 2013-05-15, Bundesamt für Sicherheit in der Informationstechnik.
[JIL-ATT-SC]	<i>Joint Interpretation Library – Attack Methods for Smartcards and Similar Devices</i> , Version 2.5, 2022-05.
[KS2011]	<i>A proposal for: Functionality classes for random number generators</i> , W. Killmann, W. Schindler, Version 2.0, 2011-09-18, T-Systems GEI GmbH and Bundesamt für Sicherheit in der Informationstechnik. Part of [AIS20] and [AIS31] .
[CC_Part1]	<i>Common Criteria, Part 1: Common Criteria for Information Technology Security Evaluation, Part 1: Introduction and general model</i> , Version 3.1, Revision 5, April 2017, CCMB-2017-04-001.
[CC_Part2]	<i>Common Criteria, Part 2: Common Criteria for Information Technology Security Evaluation, Part 2: Security functional components</i> , Version 3.1, Revision 5, April 2017, CCMB-2017-04-002.
[CC_Part3]	<i>Common Criteria, Part 3: Common Criteria for Information Technology Security Evaluation, Part 3: Security assurance components</i> , Version 3.1, Revision 5, April 2017, CCMB-2017-04-003.
[CEM]	<i>Common Methodology for Information Technology Security Evaluation, Evaluation Methodology</i> , Version 3.1, Revision 5, April 2017, CCMB-2017-04-004.
[PP]	<i>Security IC Platform Protection Profile with Augmentation Packages</i> , Version 1.0, registered and certified by Bundesamt für Sicherheit in der Informationstechnik (BSI) under the reference BSI-PP-0084-2014
[DSheet]	<i>NXP Secure Smart Card Controller N7121 – Overview</i> , Product data sheet
[DSheet_InSet]	<i>NXP Secure Smart Card Controller N7121 – Instruction Set Manual</i> , Product data sheet addendum
[DSheet_WDS]	<i>N7121 Wafer and delivery specification</i> , Product data sheet addendum
[DSheet_OEF]	<i>SmartMX3 family P71D321 Dedicated type creation</i> , Product data sheet addendum
[DSheet_CHM]	<i>NXP Secure Smart Card Controller N7121 – Chip Health Mode</i> , Product data sheet addendum
[DSheet_Periph]	<i>NXP Secure Smart Card Controller N7121 – Peripheral Configuration and Use</i> , Product data sheet addendum
[DSheet_MMU]	<i>NXP Secure Smart Card Controller N7121 – MMU Configuration and NXP Firmware Interface Specification</i> , Product data sheet addendum
[DSheet_FL]	<i>NXP Secure Smart Card Controller N7121 – Flashloader OS</i> , Product data sheet addendum
[DSheet_LibInt]	<i>NXP Secure Smart Card Controller N7121 – Shared OS Libraries</i> , Product data sheet addendum
[DSheet_SMOS]	<i>NXP Secure Smart Card Controller N7121 – NXP System Mode OS</i> , Product data sheet addendum

[Spec_and_Design]	<i>NXP Secure Smart Card Controller N7121, Specification and Design Documentation</i>
[Lifecycle]	<i>NXP N7121 B1 Hardmarco - Lifecycle Documentation, Report</i>
[UM_RNG]	<i>N7121 Crypto Library – RNG Library, User Manual</i>
[UM_SymCfg]	<i>N7121 Crypto Library – Symmetric Cipher Library (SymCfg), Preliminary user manual</i>
[UM_KeyStore]	<i>N7121 Crypto Library – KeyStoreMgr Library, User Manual</i>
[UM_SymUtils]	<i>N7121 Crypto Library – Utils Library, User Manual</i>
[UM_RSA]	<i>N7121 Crypto Library – RSA Library, User Manual</i>
[UM_RSASKeyGen]	<i>N7121 Crypto Library – RSA Key Generation Library, User Manual</i>
[UM_ECC]	<i>N7121 Crypto Library – ECC over GF(p) Library, User Manual</i>
[UM_SHA]	<i>N7121 Crypto Library – SHA Library, User Manual</i>
[UM_HASH]	<i>N7121 Crypto Library – HASH Library, User Manual</i>
[UM_AsymUtils]	<i>N7121 Crypto Library – UtilsAsym Library, User Manual</i>
[UM_KoreanSeed]	<i>N7121 Crypto Library – KoreanSeed Library, User Manual</i>
[GOM]	<i>UM12352, N7121 Information on Guidance and Operation, User manual</i>
[GOM_CL]	<i>UM12237: Information on Guidance and Operation, User manual</i>
[PUF]	<i>PUF Key derivation function specification, NXP Semiconductors, BUID, 2014.</i>
[ALGO]	<i>Bekanntmachung zur elektronischen Signatur nach dem Signaturgesetz und der Signaturverordnung (Übersicht über geeignete Algorithmen), Stand: 2016-03-17, Veröffentlicht: BAnz AT 14.04.2016 B11, Bundesnetzagentur für Elektrizität, Gas, Telekommunikation, Post und Eisenbahnen.</i>
[ANSSI 2011]	<i>ANSSI 2011: http://www.legifrance.gouv.fr/affichTexte.do;jsessionid=?cidTexte=JORFTEXT000024668816</i>
[ANSI X9.62-1999]	<i>ANSI X9.62-1999: Public Key Cryptography for the Financial Services Industry: the Elliptic Curve Digital Signature Algorithm (ECDSA), American National Standards Institute (ANSI), 1999.</i>
[ANSI X9.62-2005]	<i>ANSI X9.62-2005: Public Key Cryptography for the Financial Services Industry: the Elliptic Curve Digital Signature Algorithm (ECDSA), American National Standards Institute (ANSI), 2005.</i>
[ANSI X9.63]	<i>ANSI X9.63: Public Key Cryptography for the Financial Services Industry, Key Agreement and Key Transport Using Elliptic Curve cryptography, American National Standards Institute (ANSI), January 2011.</i>
[BN]	<i>TCG Algorithm Registry/Family "2.0": Level 00 Revision 01.22, February 9, 2015.</i>
[RFC 5639]	<i>RFC 5639: J. Merkle, ECC Brainpool Standard Curves and Curve Generation, BSI, March 2010.</i>
[SEC 2]	<i>SEC 2: Standards for Efficient Cryptography, SEC 2: Recommended Elliptic Curve Domain Parameters, Certicom Research, Version 1.0, September 20, 2000.</i>
[TU]	<i>TU Darmstadt: Cryptographically secure elliptic curves over GF(p) generated with complex multiplication by our Elliptic Curve Cryptography Group with the OID prefix 1.3.6.1.4.1.8301.3.1.2.9.0, http://www.flexiproducer.de/CurveOIDs.html</i>
[BAnz AT 30.01.2015 B3]	<i>Bundesnetzagentur für Elektrizität, Gas, Telekommunikation, Post und Eisenbahnen: Bekanntmachung zur elektronischen Signatur nach dem Signaturgesetz und der Signaturverordnung (Übersicht über geeignete Algorithmen), German "Bundesanzeiger", BAnz AT 30.01.2015 B3.</i>

[FIPS 180-4]	<i>FIPS PUB 180-4 Federal Information Processing Standards Publication Secure Hash Standard (SHS)</i> , August 2015, Information Technology Laboratory National Institute of Standards and Technology.
[FIPS 186-4]	<i>FIPS PUB 186-4 Federal Information Processing Standards Publication Digital Signature Standard (DSS)</i> , July 2013, Information Technology Laboratory National Institute of Standards and Technology.
[FIPS 197]	<i>Federal Information Processing Standards Publication 197, Announcing the ADVANCED ENCRYPTION STANDARD (AES)</i> , 2001-11-26, National Institute of Standards and Technology (NIST).
[IEEE Std 1363]	<i>IEEE Std 1363™-2000: IEEE Standard Specifications for Public-Key Cryptography</i> , 2005-12-12, IEEE Computer Society.
[ISO/IEC 14888-3]	<i>ISO/IEC 14888-3:2015: Information technology – Security techniques – Digital signatures with appendix - Part 3: Discrete logarithm based mechanisms</i> , 2016.
[ISO/IEC 9797-1]	<i>ISO 9797-1: Information technology – Security techniques - Message Authentication Codes (MACs) - Part 1: Mechanisms using a block cipher</i> , 1999-12, ISO/IEC.
[ISO 11568-4]	<i>ISO 11568-4: Banking – Key management (retail) – Part 4: Asymmetric cryptosystems – Key management and life cycle</i> , 2007
[ISO/IEC 11770-3]	<i>ISO/IEC 11770-3:2015: Information technology – Security techniques - Key management - Part 3: Mechanisms using asymmetric techniques</i> , 2015, ISO/IEC.
[NIST SP 800-38A]	<i>NIST Special Publication 800-38A, Recommendation for BlockCipher Modes of Operation</i> , National Institute of Standards and Technology (NIST), Technology Administration, U.S. Department of Commerce.
[NIST SP 800-38B]	<i>NIST Special Publication 800-38B, Recommendation for BlockCipher Modes of Operation: The CMAC Mode for Authentication</i> , National Institute of Standards and Technology (NIST), Technology Administration, U.S. Department of Commerce.
[NIST SP 800-67]	<i>NIST Special Publication 800-67 –Revision 2, Recommendation for the Triple Data Encryption Algorithm (TDEA) Block Cipher – Published November 2017</i> , National Institute of Standards and Technology (NIST), Technology Administration, U.S. Department of Commerce.
[PKCS #1]	<i>PKCS #1: RSA Cryptography Standard</i> , Version 2.2, October 27, 2012, RSA Laboratories.
[TR-03110-1]	<i>BSI TR-03110-1 Advanced Security Mechanisms for Machine Readable Travel Documents - Part 1: eMRTDs with BAC/PAVEv2 and EACv1</i> , Version 2.20, February 26, 2015, Bundesamt für Sicherheit in der Informationstechnik, Germany.
[TR-03110-2]	<i>BSI TR-03110-2 Advanced Security Mechanisms for Machine Readable Travel Documents - Part 2: Protocols for electronic IDentification, Authentication and trust Services (eIDAS)</i> , Version 2.21, December 21, 2016, Bundesamt für Sicherheit in der Informationstechnik, Germany.
[TR-03110-3]	<i>BSI TR-03110-3 Advanced Security Mechanisms for Machine Readable Travel Documents - Part 3: Common Specifications</i> , Version 2.21, December 21, 2016, Bundesamt für Sicherheit in der Informationstechnik, Germany.
[TR-03110-4]	<i>BSI TR-03110-4 Advanced Security Mechanisms for Machine Readable Travel Documents - Part 4: Applications and Document Profiles</i> , Version 2.21, December 21, 2016, Bundesamt für Sicherheit in der Informationstechnik, Germany.

9 Legal information

9.1 Definitions

Draft — A draft status on a document indicates that the content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included in a draft version of a document and shall have no liability for the consequences of use of such information.

9.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Suitability for use in non-automotive qualified products — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

Translations — A non-English (translated) version of a document, including the legal information in that document, is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Security — Customer understands that all NXP products may be subject to unidentified vulnerabilities or may support established security standards or specifications with known limitations. Customer is responsible for the design and operation of its applications and products throughout their lifecycles to reduce the effect of these vulnerabilities on customer's applications and products. Customer's responsibility also extends to other open and/or proprietary technologies supported by NXP products for use in customer's applications. NXP accepts no liability for any vulnerability. Customer should regularly check security updates from NXP and follow up appropriately. Customer shall select products with security features that best meet rules, regulations, and standards of the intended application and make the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP.

NXP has a Product Security Incident Response Team (PSIRT) (reachable at PSIRT@nxp.com) that manages the investigation, reporting, and solution release to security vulnerabilities of NXP products.

9.3 Trademarks

Notice: All referenced brands, product names, service names, and trademarks are the property of their respective owners.

NXP — wordmark and logo are trademarks of NXP B.V.

DESFire — is a trademark of NXP B.V.

MIFARE — is a trademark of NXP B.V.

Tables

Tab. 1.	Revision history	2	Tab. 14.	Security objectives for the Operational Environment	31
Tab. 2.	Memories of the TOE	6	Tab. 15.	Security Objectives (PP and ST) vs. Security Problem Definition (PP and ST)	32
Tab. 3.	TOE configuration options	6	Tab. 16.	Rationales for the assignments between the Security problem definition and the Security objectives not already covered in the Protection Profile	33
Tab. 4.	TOE deliverables of the hard macro	7	Tab. 17.	Subjects, objects as well as related operations and attributes of the Loader Policy	41
Tab. 5.	Instantiation specific IC Dedicated Software for Release package R1, R3 and R4	13	Tab. 18.	SARs for this ST	59
Tab. 6.	Instantiation specific IC Dedicated Software for Release package R2, R3 and R4	14	Tab. 19.	Mapping of the Security Objectives for the TOE to the Security Functional Requirements for the TOE	60
Tab. 7.	Fab and Crypto Library Deliverables for Release package R1, R2, R3 and R4	14	Tab. 20.	Dependencies of the Security Functional Requirements for the TOE	63
Tab. 8.	Threats defined in Protection Profile	25	Tab. 21.	SARs refined in PP and their effect on this ST	67
Tab. 9.	Additional threats defined in this Security Target	25	Tab. 22.	Portions of the TSF	70
Tab. 10.	Security policies defined in the Protection Profile	26	Tab. 23.	Mapping of SFRs to portions of the TSF	71
Tab. 11.	Assumptions defined in the Protection Profile	27			
Tab. 12.	Security objectives of the TOE defined in the Protection Profile	29			
Tab. 13.	Security Objectives of the Security IC Embedded Software Development defined in Protection Profile	31			

Figures

Fig. 1.	Block diagram of the TOE	15	Fig. 3.	Software components of the TOE	18
Fig. 2.	TOE modes overview	16			

Contents

1	Introduction	3	6.1.4	Further Security Functional Requirements – Cryptographic Library (optional)	46
1.1	ST reference	3	6.1.4.1	Library Support for TDES and AES (optional)	46
1.2	TOE reference	3	6.1.4.2	Library Support for Random-Number Generation (optional)	48
1.3	TOE overview	3	6.1.4.3	Library Support for RSA (optional)	50
1.3.1	Hardware	3	6.1.4.4	Library Support for Elliptic Curve Cryptography (optional)	53
1.3.2	Software	3	6.1.4.5	Library Support for Hashing (optional)	55
1.3.3	Documentation	4	6.1.5	Further Security Functional Requirements – PUF (optional)	56
1.3.4	Usage and major security functionality of the TOE	4	6.1.6	Further Security Functional Requirements – Self-tests	57
1.3.5	TOE type	5	6.1.7	Further Security Functional Requirements – Management Functions	57
1.3.6	Required non-TOE hardware/software/firmware	5	6.1.8	Further Security Functional Requirements – Access Control Policy	57
1.4	TOE description	6	6.2	Security assurance requirements	58
1.4.1	Evaluated configurations and TOE components	6	6.3	Security requirements rationale	60
1.4.2	Physical scope of the TOE	14	6.3.1	Rationale for the Security Functional Requirements	60
1.4.3	Logical scope of the TOE	15	6.3.2	Dependencies of the Security Functional Requirements	63
1.4.3.1	Hardware description	15	6.3.3	Refinements of the TOE Security Assurance Requirements	66
1.4.3.2	Software description	18	6.3.4	Rationale for the Security Assurance Requirements	68
1.4.4	Security during Development and Production	21	6.3.5	Security requirements are internally consistent	69
1.4.5	TOE intended usage	21	7	TOE summary specification	70
1.4.6	Interface of the TOE	22	7.1	Portions of the TOE Security Functionality	70
2	Conformance claims	23	7.2	TOE summary specification rationale	70
2.1	Package claim	23	7.2.1	Mapping of Security Functional Requirements and TOE security functionality	70
2.2	PP claim	23	7.2.2	Security Architectural Information	73
2.3	Conformance claim rationale	24	8	References	74
3	Security problem definition	25	9	Legal information	77
3.1	Description of assets	25			
3.2	Threats	25			
3.3	Organizational security policies	26			
3.4	Assumptions	27			
4	Security objectives	29			
4.1	Security objectives of the TOE	29			
4.2	Security objectives of the security IC embedded software development	31			
4.3	Security objectives for the Operational Environment	31			
4.4	Security objectives rationale	32			
5	Extended components definition	35			
5.1	Cryptographic Key Derivation (FCS_CKM.5)	35			
6	Security requirements	36			
6.1	Security functional requirements	36			
6.1.1	Security Functional Requirements of the PP	36			
6.1.2	Flash Loader (partly optional)	41			
6.1.2.1	Loader Package 1 defined in the PP	42			
6.1.2.2	Loader Package 2 defined in the PP (optional)	43			
6.1.3	Hardware Support for TDES and AES	45			
6.1.3.1	Package TDES defined in PP	45			
6.1.3.2	Package "AES" defined in PP	46			

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.